FORMAT 3-part hand tap set HSS metric fine type 1618





Design: HSS-E, DIN 352, tolerance range ISO 2/6H, type INOX, bright surface.

3 piece set consisting of roughing tap with point form A (6?8 threads), second tap with point form D (3.5?5 threads) and finish tap with point form C (2?3 threads).

Application: For regular metric threads according to ISO DIN 13. Particularly suitable for high strength materials up to 1200 N/mm² in strength and rust-free and acid-resistant steels.

Characteristics

Kind of thread: Metric DIN standard: 352

Kind of thread	Thread size metric (M)	Pitch inner thread	DIN standard	Material	Total length	Article
		mm			mm	
Metric	2	0.4	352	HSS-co	36	23411694
Metric	2.5	0.45	352	HSS-co	40	23411695
Metric	3	0.5	352	HSS-co	40	23411696
Metric	3.5	0.6	352	HSS-co	45	23411697
Metric	4	0.7	352	HSS-co	45	23411698
Metric	5	0.8	352	HSS-co	50	23411699
Metric	6	1	352	HSS-co	50	23411700
Metric	8	1.25	352	HSS-co	56	23411701
Metric	10		352	HSS-co		23411702
Metric	12	1.75	352	HSS-co	75	23411703
Metric	14	2	352	HSS-co	80	23411704
Metric	16	2	352	HSS-co	80	23411705
Metric	20	2.5	352	HSS-co	95	23411706

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

ERIKS

PR_EC002155_0900_EN_19.05.2024