

3M Trizact sanding sleeve

Design: Full resin-bonded aluminium oxide grain on heavy, tear-resistant, semi-flexible cloth backing for long service life. Uniform structure of the abrasive grain (pyramidal structure of the grinding surface) for finishing touches, constant roughness, with grinding aid for a cool touch. Measurements ($L \times W \times \emptyset$) 289 x 100 x 90 mm.

Application: For use on burnishing machines using mounting drums within the Match and Finish systems. For uniform, surface-finish quality with smooth patina in fewer operations.

Note: Mounting drum, pneumatic (Order No. 8458 1000) mounting drum, soft (Order No. 8458 1010)

Not suitable for use with hard mounting drum!

Description	Article
Trizact abrasive sleeves 237AA 100x289mm A160	12064142
Trizact abrasive sleeves 237AA 100x289mm A30	12064145
Trizact abrasive sleeves 237AA 100x289mm A65	12064144
Trizact abrasive sleeves 237AA 100x289mm A80	12064143

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

ERIKS

PR_EC002196_0083_MVB_EN_06.05.2024