



FORMAT HSS die with UNC thread type 1820



Design: HSS, EN 22568, tolerance range 2A, closed, pre-slotted form with single sided spiral point, with spiral point form on both sides from no. 5.

Application: For UNC coarse thread ANSI B1.1
UNF precision thread ANSI B1.1.

Kind of thread	Thread size in	Pitch outer thread in	Material	Article
UNC	1/4	20	HSS	23104929
UNC	5/16	18	HSS	23412735
UNC	3/8	16	HSS	23412736
UNC	1/2	13	HSS	23412738
UNC	9/16	12	HSS	23412739
UNC	5/8	11	HSS	23412740
UNC	3/4	10	HSS	23412741
UNC	7/8	9	HSS	23412742
UNC	1	8	HSS	23412743
UNC	7/16	14	HSS	23412737
UNC			HSS	23412726
UNC			HSS	23412733
UNC			HSS	23412730
UNC			HSS	23412727
UNC			HSS	23412732
UNC			HSS	23412729
UNC			HSS	23412728
UNC			HSS	23412731
UNC			HSS	23412725

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.