

DIN6798A Flat serrated lock washer with external teeth Spring steel

Characteristics Series: DIN 6798A Surface protection: Untreated DIN standard: 6798A





Material	Surface protection	Inner diameter	Outer diameter	Suitable for bolt size metric (M)	Model	Article
		mm	mm			
Carbon steel	Untreated	3.2	6	3	Closed external toothing	11787349
Carbon steel	Untreated	3.2	6	3	Closed external toothing	11787360
Carbon steel	Untreated	4.3	8	4	Closed external toothing	11787362
Carbon steel	Untreated	4.3	8	4	Closed external toothing	11787350
Carbon steel	Untreated	5.3	10	5	Closed external toothing	23692065
Carbon steel	Untreated	6.4	11	6	Closed external toothing	23692066
Carbon steel	Untreated	8.4	15	8	Closed external toothing	11787366
Carbon steel	Untreated	10.5	18	10	Closed external toothing	11787351
Carbon steel	Untreated	13	20.5	12	Closed external toothing	11787352
Carbon steel	Untreated	15	24	14	Closed external toothing	23692071
Carbon steel	Untreated	17	26	16	Closed external toothing	11787353
Carbon steel	Untreated	21	33	20	Closed external toothing	23692069
Carbon steel	Untreated	23	36	22	Closed external toothing	11787354
Carbon steel	Untreated	31	48	30	Closed external toothing	11787356

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.



ERIKS

ERIKS BV