


ISO7380-2 Hexagon socket button head screw with flange Stainless steel A2



Characteristics

Series: ISO 7380

Material quality: Stainless steel A2

Surface protection: Untreated

Kind of thread: Metric

Head form: Round head

ISO standard: 7380

Screwing system: Internal hexagon

Material	Thread size metric (M...)	Pitch thread	Length	Head height	Screw-in length	Article
		mm	mm	mm	mm	
Stainless steel	4	0.7	6	2.2	16	23263410
Stainless steel	4	0.7	10	2.2	16	23263412
Stainless steel	4	0.7	12	2.2	16	23263413
Stainless steel	5	0.8	8	2.75	30	23263418
Stainless steel	5	0.8	10	2.75	30	23263419
Stainless steel	5	0.8	12	2.75	30	23263420
Stainless steel	5	0.8	16	2.75	30	23263421
Stainless steel	6	1	8	3.3	30	23263425
Stainless steel	6	1	10	3.3	30	23263426
Stainless steel	6	1	12	3.3	30	23263427
Stainless steel	6	1	16	3.3	30	23263428
Stainless steel	6	1	16			23732282
Stainless steel	6	1	20	3.3	30	23263429
Stainless steel	6	1	25	3.3	30	23263430
Stainless steel	6	1	30	3.3	30	23263431
Stainless steel	6	1	35	3.3	30	23263432
Stainless steel	8	1.25	10	4.4	40	23263434
Stainless steel	8	1.25	12	4.4	40	23263435
Stainless steel	8	1.25	16	4.4	40	23263436
Stainless steel	8	1.25	20	4.4	40	23263437
Stainless steel	8	1.25	25	4.4	40	23263438
Stainless steel	8	1.25	40	4.4	40	23263441

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.