



REMA Bow shackle G 4161

Galvanized steel with a high tensile strength suitable for temperatures between -20 ° C and + 200 ° C


Equipped with screwpin

Marking: According to standard, CE-marked

Standard: EN 13889

Safety factor: 6

Grade: 6



Description	Article
Bow shackle galvanised steel with screwpin G-4161 0,75t safety factor 6	23795477
Bow shackle galvanised steel with screwpin G-4161 1,0t safety factor 6	23795478
Bow shackle galvanised steel with screwpin G-4161 1,5t safety factor 6	23795479
Bow shackle galvanised steel with screwpin G-4161 12t safety factor 6	23795486
Bow shackle galvanised steel with screwpin G-4161 13,5t safety factor 6	23795487
Bow shackle galvanised steel with screwpin G-4161 8,5t safety factor 6	23795484
Bow shackle galvanised steel with screwpin G-4161 -17t safety factor 6	23795488
Bow shackle galvanised steel with screwpin G-4161 -35t safety factor 6	23795490

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.