

OVENTROP Fill and drain valve Series: Optiflex Type: 447 Brass External thread (BSPP)/Hose tail



Characteristics

Series: Optiflex

Type: 447

Norm: EN (DIN)

Execution: Fill/drain cock

Construction type: Straight

Housing material: Brass

Connection: External thread (BSPP)

Connection 2: Hose tail

Self-locking: Yes

Type of disc: Ball

Maximum medium temperature (continuous): 120 °C


Maximum pressure at 20 °C: 16 bar

With operating key: Yes

With sealing cap: Yes

Application

- Recommended in: Utilities



DN ["]	L1 mm	L2 mm	H mm
3/8	38,5	72	31
1/2	38,5	72	31
3/4	49,5	92	34
1	60,5	124	53

Min./Max.	Press./Temp.
Max.working pressure	16bar
Max. temperature	120°C

Nominal inner diameter	Diameter, hose connector mm	Pressure rating	Face to Face length mm	Operation	Article
3/8" [10]	10	PN16	71.5	Knob	13369133
1/2" [15]	15	PN16	71.5	Knob	11811279
1/2" [15]	15	PN16	71.5	Knob	13369118
3/4" [20]	20	PN16	91.5	Knob	11811280
1" [25]	25	PN16	123.5	Knob	13369138

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.