



ARI Bellow sealed valve Series: 22.047 Type: 130 Ductile cast iron Flange PN16

ARI-FABA® type Plus ductile iron bellow sealed globe valve, SS trim, double bellow, angle form pattern, flanged connection, outside screw & yoke, non-rising hand wheel.

Area of application

General industry, power stations, flue gas purification plant, steam facilities, heating technology, district heating, thermal oil applications, ammonia plants, vacuum facilities.

Characteristics

Series: 22.047

Type: 130

Norm: EN [DIN]

Construction type: Angle pattern

Housing material: Ductile cast iron

Surface protection: Standard manufacturers coating

Connection: Flange

Flange finish: Raised face

Stem seal type: Bellows

Material disc: 1.4021+QT

Spindle material: 1.4021+QT

Primary spindle seal material: Graphite

Bellows material: 1.4571

Material bonnet: EN-JS1049

Characteristics (2)

Bonnet gasket material: Stainless steel/graphite

Actuator material: Steel

Minimum medium temperature (continuous): -10 °C

Maximum medium temperature (continuous): 350 °C

Maximum pressure difference at 20 °C: 16 bar

With position indicator: Yes

Material quality	Nominal inner diameter	Pressure rating	Face to Face norm	Face to Face length mm	Operation	Type of disc	Type of bonnet	Sealing	Kv value m³/h	Article
EN-JS1049	DN15	PN16	EN 558, Series 8	90	Hand wheel, non-rising with rising stem	Fixed disc	Bolted bonnet	Stainless steel	6	11811235
EN-JS1049	DN20	PN16	EN 558, Series 8	95	Hand wheel, non-rising with rising stem	Fixed disc	Bolted bonnet	Stainless steel	9	11811236
EN-JS1049	DN25	PN16	EN 558, Series 8	100	Hand wheel, non-rising with rising stem	Fixed disc	Bolted bonnet	Stainless steel	14	11811237
EN-JS1049	DN32	PN16	EN 558, Series 8	105	Hand wheel, non-rising with rising stem	Fixed disc	Bolted bonnet	Stainless steel	19	11811238
EN-JS1049	DN40	PN16	EN 558, Series 8	115	Hand wheel, non-rising with rising stem	Fixed disc	Bolted bonnet	Stainless steel	35	11811239
EN-JS1049	DN50	PN16	EN 558, Series 8	125	Hand wheel, non-rising with rising stem	Fixed disc	Bolted bonnet	Stainless steel	53	11811240
EN-JS1049	DN65	PN16	EN 558, Series 8	145	Hand wheel, non-rising with rising stem	Fixed disc	Bolted bonnet	Stainless steel	94	12035697
EN-JS1049	DN80	PN16	EN 558, Series 8	155	Hand wheel, non-rising with rising stem	Fixed disc	Bolted bonnet	Stainless steel	143	12035698

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Material quality	Nominal inner diameter	Pressure rating	Face to Face norm	Face to Face length	Operation	Type of disc	Type of bonnet	Sealing	Kv value	Article
				mm						
									m³/h	
EN-JS1049	DN100	PN16	EN 558, Series 8	175	Hand wheel, non-rising with rising stem	Fixed disc	Bolted bonnet	Stainless steel	245	12035699
EN-JS1049	DN100	PN16	EN 558, Series 8	175	Hand wheel, non-rising with rising stem	Screw down non-return disc with spring	Bolted bonnet	Stainless steel	245	13288259

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.