


ECON® Globe valve Type: 1272 Low zinc bronze PN16



Application

- Water, oil, air, gas, etc.. on board ships.
- These valves offer good resistance to corrosive action of seawater, freshwater and wastewater.
- Cunifer piping systems.

Specifications

- Acceptance by various inspection authorities possible.
- Also available with regulating disc, with or without position indicator.

Characteristics

Type: 1272

Norm: EN (DIN)

Construction type: Straight

Housing material: Low zinc bronze

Surface protection: Standard manufacturers coating

Connection: Flange

Flange finish: Flat face

Stem seal type: Gland seal

With backflow safeguard: No

Material disc: 2.1086 (RG10)

Spindle material: CW453K (CuSn8)

Primary spindle seal material: Graphite

Material bonnet: G-CuSn10Zn (Rg10)

Characteristics [2]

Bonnet gasket material: Graphite

Actuator material: Cast iron

Minimum medium temperature (continuous): -10 °C

Maximum medium temperature (continuous): 200 °C

Maximum pressure difference at 20 °C: 16 bar

With position indicator: No

With drain: No

Material quality	Nominal inner diameter	Pressure rating	Face to Face norm	Face to Face length	Operation	Type of disc	Type of bonnet	Sealing	Kv value	Article
				mm					m³/h	
G-CuSn10Zn (Rg10)	DN15	PN16	Manufacturer standard	120	Hand wheel, rising with rising stem	Fixed disc	Bolted bonnet	Low zinc bronze	6	13360056
G-CuSn10Zn (Rg10)	DN15	PN16	Manufacturer standard	120	Hand wheel, rising with rising stem	Screw down non-return disc without spring	Bolted bonnet	Low zinc bronze	6	13360068
G-CuSn10Zn (Rg10)	DN40	PN16	Manufacturer standard	155	Hand wheel, rising with rising stem	Fixed disc	Bolted bonnet	Low zinc bronze	33	13360060
G-CuSn10Zn (Rg10)	DN40	PN16	Manufacturer standard	155	Hand wheel, rising with rising stem	Screw down non-return disc without spring	Bolted bonnet	Low zinc bronze	33	13360072
G-CuSn10Zn (Rg10)	DN50	PN16	Manufacturer standard	180	Hand wheel, rising with rising stem	Fixed disc	Bolted bonnet	Low zinc bronze	52	13360061
G-CuSn10Zn (Rg10)	DN100	PN16	Manufacturer standard	270	Hand wheel, rising with rising stem	Fixed disc	Bolted bonnet	Low zinc bronze	207	13360064
G-CuSn10Zn (Rg10)	DN125	PN16	Manufacturer standard	320	Hand wheel, rising with rising stem	Fixed disc	Bolted bonnet	Low zinc bronze	325	13360065
G-CuSn10Zn (Rg10)	DN150	PN16	Manufacturer standard	370	Hand wheel, rising with rising stem	Screw down non-return disc without spring	Bolted bonnet	Low zinc bronze	465	13360077

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.