


S & S Globe valve Type 197 stainless steel entry above the valve pneumatic flange EN (DIN) PN40



Characteristics

Function: Two-way valve
Norm: EN (DIN)
Construction type: Straight
Housing material: Stainless steel
Material quality: 1.4408
Process connection: Flange
Size process connection: DN50
Standard connection: EN 1092-1
Flange finish: Raised face
Face to Face norm: EN 558, Series 1
Type of disc: Fixed disc
Actuation: Pressure above the valve
Type of actuator: Pneumatic piston
Type of drive: Single acting
Function actuator: Spring closing

Position indicator: Yes
Stem seal type: Roof cuffs
Primary spindle seal material: PTFE
Material disc: 1.4571
Spindle material: 1.4571
Material bonnet: 1.4408
Bonnet gasket material: Fiber Gasket
Approvals: TA-Luft according IN EN ISO 15848-1 and VDI 2440

Application

- Neutral liquids.
- Neutral gases.
- Vapours.

Nominal inner diameter	Pressure rating	Kv value	Closing pressure	Actuator	Pilot pressure	Actuator material	Max. viscosity	Medium temperature	Ambient temperature	Article
		m ³ /h	bar							
DN15	PN40	3.1	40	R50	10 bar	Brass chromium-plated	600	-30 / 170	-30 / 60	12267655
DN20	PN40	6.5	38	R50	10 bar	Brass chromium-plated	600	-30 / 170	-30 / 60	12267656
DN25	PN40	12	20	R50	10 bar	Brass chromium-plated	600	-30 / 170	-30 / 60	12267657
DN32	PN40	17.5	12	R50	10 bar	Brass chromium-plated	600	-30 / 170	-30 / 60	12267658
DN32	PN40	17.5	35	R80	10 bar	Brass chromium-plated	600	-30 / 170	-30 / 60	12267659
DN40	PN40	25	23	R80	10 bar	Brass chromium-plated	600	-30 / 170	-30 / 60	12267660
DN50	PN40	40	14	R80	10 bar	Brass chromium-plated	600	-30 / 170	-30 / 60	12267661
DN50	PN40	40	15	R125	10 bar	Aluminium	600	-30 / 170	-30 / 60	12267662

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.