

AQUATHERM Straight stopcock in PP-R - welding sockets

Characteristics

Construction type: Straight Housing material: PP-R

Connection: Plastic welded sleeve

| Nominal inner diameter | External tube diameter of connection | Pressure rating | Face to Face length | Operation | Type of disc | Type of bonnet | Sealing | Article |
|------------------------|--------------------------------------|-----------------|------------------------|------------|--------------|----------------|---------|----------|
| DN15 | mm 20 | PN20 | 41 | Hand wheel | Fixed disc | Screwed | Rubber | 11086740 |
| DN20 | 25 | PN20 | 44 | Hand wheel | Fixed disc | Screwed | Rubber | 11086862 |
| DN25 | 32 | PN20 | 62 | Hand wheel | Fixed disc | Screwed | Rubber | 11086883 |
| DN32 | 40 | PN20 | 79 | Hand wheel | Fixed disc | Screwed | Rubber | 11086884 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

PR_EC010120_0086_EN_18.05.2024