



ARI Globe valve Series: 48.005....40 Type: 3419 Steel Butt weld PN160

Characteristics

Series: 48.005....40

Type: 3419

Norm: EN (DIN)

Construction type: Straight

Housing material: Steel

Surface protection: Standard manufacturers coating

Connection: Butt weld

Standard welding connection: EN 12627

Stem seal type: Gland seal

Material disc: 1.4021+QT

Spindle material: 1.4021+QT

Primary spindle seal material: Graphite

Material bonnet: 1.0460

Characteristics (2)

Bonnet gasket material: Stainless steel/graphite

Actuator material: Cast iron

Minimum medium temperature (continuous): -10 °C

Maximum medium temperature (continuous): 450 °C

Maximum pressure difference at 20 °C: 160 bar

Material quality	Nominal inner diameter	Pressure rating	Face to Face norm	Face to Face length	Operation	Type of disc	Type of bonnet	Sealing	Kv value	Article
				mm					m³/h	
1.0460	DN10	PN160	EN 12982, Serie 65	150	Hand wheel, rising with rising stem	Fixed disc	Bolted bonnet	Stellite 21	2.7	12711992
1.0460	DN15	PN160	EN 12982, Serie 65	150	Hand wheel, rising with rising stem	Fixed disc	Bolted bonnet	Stellite 21	4.2	12711993
1.0460	DN20	PN160	EN 12982, Serie 65	150	Hand wheel, rising with rising stem	Fixed disc	Bolted bonnet	Stellite 21	6.4	12711994
1.0460	DN25	PN160	EN 12982, Serie 65	160	Hand wheel, rising with rising stem	Fixed disc	Bolted bonnet	Stellite 21	8.6	12711995
1.0460	DN32	PN160	EN 12982, Serie 65	180	Hand wheel, rising with rising stem	Fixed disc	Bolted bonnet	Stellite 21	21.8	12711996
1.0460	DN40	PN160	EN 12982, Serie 65	210	Hand wheel, rising with rising stem	Fixed disc	Bolted bonnet	Stellite 21	24.2	12711997
1.0460	DN50	PN160	EN 12982, Serie 65	250	Hand wheel, rising with rising stem	Fixed disc	Bolted bonnet	Stellite 21	33	12711998

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.