


HONEYWELL Pressure reducing valve Type 141B series D16 bronze flange



Characteristics

Series: D16
Type: 141B
Model: Direct-acting
Connection: Flange
Maximum inlet pressure: 25 bar
Medium temperature: 0 / 65 °C
Suitable for gases: 1
Housing material: Bronze
Material quality: Rg 5
Material disc: Synthetic material
Seat material: Synthetic material

Characteristics (2)

Membrane material: NBR
Spring material: Spring steel
Material spring bonnet: Brass
Filter element material: Stainless steel
With couplers: No
Backflow preventer: No

Nominal inner diameter	Capacity type	Kvs value m³/h	Reduced pressure range bar	Article
DN15	Standard	3	1.5 / 12	11810578
DN20	Standard	3.3	1.5 / 12	11810579
DN25	Standard	8.5	1.5 / 12	11810580
DN32	Standard	10.1	1.5 / 12	11810581
DN40	Standard	13.5	1.5 / 12	11810582

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.