



GF Y-filter Series: 305 PVC-U (transparent) Glued end

Characteristics

Series: 305

Housing material: PVC-U (transparent)

Connection: Glued end

Minimum medium temperature (continuous): 0 °C

Maximum medium temperature (continuous): 60 °C

External tube diameter of connection mm	Pressure rating	With measuring connections	With drain plug	O-ring material	Article
20	PN10	No	No	EPDM	10059000
20	PN10	No	No	FPM (FKM)	10059001
25	PN10	No	No	EPDM	10059002
32	PN10	No	No	EPDM	10059004
32	PN10	No	No	FPM (FKM)	10059005
40	PN10	No	No	EPDM	10059006
40	PN10	No	No	FPM (FKM)	10059007
50	PN10	No	No	FPM (FKM)	10059009
50	PN10	No	No	EPDM	10059008
63	PN10	No	No	EPDM	10059010
63	PN10	No	No	FPM (FKM)	10059011
75	PN10	No	No	EPDM	10059012
75	PN10	No	No	FPM (FKM)	10059013
90	PN10	No	No	EPDM	10059014
90	PN10	No	No	FPM (FKM)	10059015

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.