

FLEXION Elbow adaptor, nickel plated brass, male-female thread



Characteristics
Series: W89A
Type: ADPT-B-L
Operation temperature: -40 / 150 °C
Operating pressure: -0.95 / 60 bar
Maximum operating pressure [Bar]: 60 bar

Manufacturer ID	Material	Threaded connection 1	Connection 1 thread size	Threaded connection 2	Connection 2 thread size	Article
W89A-12136	Brass, Nickel-plated	External thread BSPT (R)	1/2	Internal thread BSPP (G)	1/2	24207892
W89A-12130	Brass, Nickel-plated	External thread BSPT (R)	1/4	Internal thread BSPP (G)	1/4	24207503
W89A-12128	Brass, Nickel-plated	External thread BSPT (R)	1/8	Internal thread BSPP (G)	1/8	14378239
W89A-12140	Brass, Nickel-plated	External thread BSPT (R)	1	Internal thread BSPP (G)	1	24208775
W89A-12138	Brass, Nickel-plated	External thread BSPT (R)	3/4	Internal thread BSPP (G)	3/4	24201054
W89A-12134	Brass, Nickel-plated	External thread BSPT (R)	3/8	Internal thread BSPP (G)	3/8	24200515
W89A-12126	Brass, Nickel-plated	External thread BSPT (R)	M 5	Internal thread BSPP (G)	M 5	24203231

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.