

FLEXION Elbow adaptor, nickel plated brass, female-female thread



Characteristics

- Series:** W89A
Type: ADPT-B-L
Operation temperature: -40 / 150 °C
Operating pressure: -0.95 / 60 bar
Maximum operating pressure [Bar]: 60 bar

Manufacturer ID	Material	Threaded connection 1	Connection 1 thread size	Threaded connection 2	Connection 2 thread size	Article
W89A-12150	Brass, Nickel-plated	Internal thread BSPP (G)	1/2	Internal thread BSPP (G)	1/2	14378240
W89A-12146	Brass, Nickel-plated	Internal thread BSPP (G)	1/4	Internal thread BSPP (G)	1/4	24211300
W89A-12154	Brass, Nickel-plated	Internal thread BSPP (G)	1	Internal thread BSPP (G)	1	24202011
W89A-12152	Brass, Nickel-plated	Internal thread BSPP (G)	3/4	Internal thread BSPP (G)	3/4	24201210
W89A-12148	Brass, Nickel-plated	Internal thread BSPP (G)	3/8	Internal thread BSPP (G)	3/8	24203925
W89A-12142	Brass, Nickel-plated	Internal thread BSPP (G)	M 5	Internal thread BSPP (G)	M 5	24207192

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.