



FLEXION Partition duct link, Nickel Plated Brass, Female/ Female

Characteristics

- Series:** W89A
- Type:** BULK-B
- Operation temperature:** -40 / 150 °C
- Operating pressure:** -0.95 / 60 bar
- Maximum operating pressure [Bar]:** 60 bar

Manufacturer ID	Material	Threaded connection 1	Connection 1 thread size	Threaded connection 2	Connection 2 thread size	Article
W89A-12436	Brass, Nickel-plated	Internal thread (M)	M 5	Internal thread (M)	M 10x1	24208819
W89A-12444	Brass, Nickel-plated	Internal thread BSPP (G)	1/2	Internal thread (M)	M 28x1.5	24202177
W89A-12440	Brass, Nickel-plated	Internal thread BSPP (G)	1/4	Internal thread (M)	M 20x1.5	14378229
W89A-12438	Brass, Nickel-plated	Internal thread BSPP (G)	1/8	Internal thread (M)	M 16x1.5	24207134
W89A-12442	Brass, Nickel-plated	Internal thread BSPP (G)	3/8	Internal thread (M)	M 26x1.5	24211903

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.