ECON® Pressure gauge valve double Type 1381 stainless steel inspection flange internal/external thread

Characteristics

Type: 1381

Housing material: Stainless steel

Material quality: 1.4571 Operation: Hand wheel

Material tension socket: Stainless steel
Material swivel nut: Stainless steel



Application

• Recommended in: Chemical



| Process connection | Size process connection | Connection instrument side | Size instrument connection | Inspection connection | Pressure rating | Maximum pressure at 20 °C | Maximum medium temperature (continuous) | Primary spindle seal material | Spindle material | Article |
|--------------------|-------------------------|----------------------------|----------------------------------|--------------------------|--------------------|---------------------------------|--|-------------------------------------|---------------------|----------|
| | | | | | | bar | °C | | | |
| External thread | 1/2" BSPP(G) | Tension socket | 1/2" BSPP(G) | Flange 40 x 5 mm | PN400 | 400 | 200 | PTFE | 1.4571 | 11812227 |
| External thread | 1/2" BSPP(G) | Tension socket | 1/2" BSPP[G] | M20x1.5 | PN400 | 400 | 200 | PTFE | 1.4571 | 12528444 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

ERIKS

PR_EC010262_0019_MVD_EN_20.05.2024