



PRESSOL PREMxx pump 12 V — max. 38 litres/min

PREMxx barrel and container pump 12 V - max. 38 l/min

- **Suitable for heating oil and diesel**

For the filling of agricultural machines, construction machines, trucks, motor boats and utility vehicles

Note: Not suitable for biodiesel!

- **Extraction height 7 to 15 m**

For 200 l containers / max. 1000 l tanks, suction up to 2 m by way of integrated lever-operated cylinder pump

Barrel adapter 50.80 mm [G 2"] and M64x4a.

- **Safe handling**

Suction unit with integrated, constantly effective lifting protection (leak-proof) according to WHG

Motor with thermo protection switch (against overload, self resetting)

Illuminated power switch

- **Extensive extraction set**

Complete with 4 m extraction hose with kink protection spring and dispenser valve

1.6 m suction hose with foot filter

Description	Article
PREMxx 38l/min-12V-DC ABK-ZVABD-4m	11598483
PREMxx 38l/min-12V-DC ABK-ZVPP-4m	11598482

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.