



AKO Pinch valve Series: VF Type: 208 Pneumatic operated Flange

Characteristics

Series: VF

Norm: EN (DIN)

Housing material: Aluminium

Material quality: AISi10Mg

Surface protection: Manufacturer standard

Connection: Flange


Operation: Pneumatic operated

Minimum medium temperature (continuous): -10 °C

Maximum medium temperature (continuous): 80 °C

Application

- Recommended in: Food & Beverages, Machine Construction



Nominal inner diameter	Pressure rating	Pressure rating flange	Material code hose/sleeve	Hose/sleeve material	Maximum control pressure	Maximum pressure difference at 20 °C	Article
					bar	bar	
DN40	PN6	PN10	NR-X	NR (natural rubber)	8	6	10051530
DN50	PN6	PN10	NR-X	NR (natural rubber)	8	6	10051531
DN65	PN6	PN10	NR-X	NR (natural rubber)	8	6	10051532
DN80	PN6	PN10	NR-X	NR (natural rubber)	8	6	10051533
DN100	PN6	PN10	NR-X	NR (natural rubber)	8	6	10051534
DN125	PN6	PN10	NR-X	NR (natural rubber)	8	6	10051535
DN150	PN6	PN10	NR-X	NR (natural rubber)	8	6	10051536
DN200	PN4	PN10	NR-X	NR (natural rubber)	6	4	10051537

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.