




WILLBRANDT Compensator type 50 colour red - suitable for potable water - flanges - steel - model 'C' with movement limiters



Characteristics

Type: 50



Colour code	Face to Face length	Type	Maximum operating pressure at 20 °C	Vacuum-resistance at 20 °C	Configuration with movement limiter	Bellows inside wall material	Nominal inner diameter	Article
	mm		bar	%				
Red/DW	130	50	16	20	Yes	IIR [Butyl]	DN25	11256523
Red/DW	130	50	16	20	Yes	IIR [Butyl]	DN50	11256526
Red/DW	130	50	16	20	Yes	IIR [Butyl]	DN200	11256532
Red/DW	130	50	16	20	Yes	IIR [Butyl]	DN20	11256522
Red/DW	130	50	16	20	Yes	IIR [Butyl]	DN32	11256524
Red/DW	130	50	16	20	Yes	IIR [Butyl]	DN40	11256525
Red/DW	130	50	16	20	Yes	IIR [Butyl]	DN65	11256527
Red/DW	130	50	16	20	Yes	IIR [Butyl]	DN80	11256528
Red/DW	130	50	16	20	Yes	IIR [Butyl]	DN100	11256529
Red/DW	130	50	16	20	Yes	IIR [Butyl]	DN125	11256530
Red/DW	130	50	16	20	Yes	IIR [Butyl]	DN150	11256531
Red/DW	130	50	16	20	Yes	IIR [Butyl]	DN200	11163714
Red/DW	130	50	16	20	Yes	IIR [Butyl]	DN250	11256533
Red/DW	130	50	16	20	Yes	IIR [Butyl]	DN300	11256534
Red/DW	200	50	16	20	Yes	IIR [Butyl]	DN350	11256535
Red/DW	200	50	16	20	Yes	IIR [Butyl]	DN600	11018346
Red/DW	200	50	16	20	Yes	IIR [Butyl]	DN400	10040339
Red/DW	250	50	10	20	Yes	IIR [Butyl]	DN700	11256536
Red/DW	250	50	10	20	Yes	IIR [Butyl]	DN800	11256537
Red/DW	300	50	10	20	Yes	IIR [Butyl]	DN900	11256538
Red/DW	300	50	10	20	Yes	IIR [Butyl]	DN1000	11256539

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.