



ERIKS Back-up ring FKM

Characteristics

Material: FKM

Colour: Black

Temperature range: -20 / 200 °C

Inner diameter	Height	Thickness	Size according to AS568- BS1806-ISO3601	Article
mm	mm	mm		
0.594	1.35	1.24	009	12426206
11.48	2.18	1.35	111	12426205
13.16	1.35	1.24	014	12591471
14.66	2.18	1.35	113	11534176
14.73	1.35	1.24	015	12135173
21.08	1.35	1.24	019	12591470
22.68	1.35	1.24	020	12229137
25.86	2.18	1.35	120	12229139
40.16	2.18	1.35	129	12229140
48.18	3	1.27	225	12229163
56.03	2.18	1.35	139	12229141
57.61	4.65	1.93	331	12558742
60.88	3	1.27	229	12229164
62.38	2.18	1.35	143	12358148
63.96	2.18	1.35	144	11404310
66.83	3	1.27	231	12229142
67.13	4.65	1.93	334	12558753
79.53	3	1.27	235	11404311
82.7	3	1.27	236	12229165
89.48	4.65	1.93	341	12629919
104.93	3	1.27	243	12251502
114.45	3	1.27	246	11404313
118.19	4.65	1.93	350	12629920
124.28	3	1.27	249	12251503
127.71	4.65	1.93	353	12572018
141	5.99	2.97	433	11618263
146.51	3	1.27	256	12385905
159.46	4.65	1.93	362	11423623
165.56	3	1.27	260	12385695
172.16	4.65	1.93	364	12553599
178.26	3	1.27	262	12613125
178.51	4.65	1.93	365	12472995
184.76	5.99	2.97	442	12588755
191.21	4.65	1.93	367	12426204
203.91	4.65	1.93	369	12472998
229.06	3	1.27	270	12631890
457.4	4.65	1.93	387	12490600

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.