



ERIKS Gland packing Hamar material type Ralon



Packing braided from Ramie fiber with PTFE impregnation

Main areas of application:

Pumps, Agitators and Mixers. Suitable for: Paper and pulp, shipping industry, sewage plants and water treatment industries

Characteristics:

- Universal packing for low temperatures
- Cost effective
- Packing is protected against rotting
- Excellent at sealing fluids which contain solid substances
- Shaft hardness of HRC 45 is recommended

This packing is certified by Fraunhofer-Institute for Process Engineering and Packaging ,Germany, as suitable for use in food processing machinery according to FDA US 21 CFR 170.3 (i) and to article 3 of EU directive 1935/2004.

Parameters:

- Pumps : 40 bar – 12.5 m/s
- Plungers: 400 bar – 2 m/s.

Characteristics

Impregnation material: PTFE/lubricant

Width mm	Height mm	Article
22	22	10034073
25	25	10034071
6	6	10034080
8	8	10034081
10	10	10034079
12.5	12.5	10034078
14	14	10034077
15	15	10034076
16	16	10034074
19	19	10034072
20	20	10034075

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.