



SPIRAX SARCO Water separator Type: 1089 Series: S5 steel flange

Characteristics

Series: S5

Type: 1089

Max. operating pressure: 35.9 bar

Housing material: Cast steel

Material quality: 1.0619 + N/ASTM A216 WCB

Suitable for compressed air: Yes


Suitable for steam: Yes

Application

- Steam installations. Compressed air systems.

Operating Principle

- Moisture in the systems causes excessive wear and water hammer. A water separator, mounted for example for control valves and measuring instruments, effectively collects any moisture that may be present, which is then discharged via a condensate separator. The service life of valuable equipment is significantly extended by the use of water separators.



DN ["/mm]	A mm	B mm	C mm	D mm	F ["]	H ["]	Weight [kg]	Volume [liters]
15	95	162	229	204	1	½	4,5	0,85
20	105	158	345	212	1	½	5	1,03
25	115	184	387	260	1	½	9,5	2,6
32	140	209	438	274	1	½	19	4,6
40	150	221	508	310	1	1	27	7,9
50	165	221	558	310	1	1	29	8,7
65	185	270	663	419	1	¾	70	18
80	200	329	764	489	1	¾	90	32

Connection	Nominal inner diameter	Pressure rating	Maximum medium temperature (continuous) °C	Article
Flange	DN15	PN40	425	11811992
Flange	DN20	PN40	425	11811993
Flange	DN25	PN40	425	11811994
Flange	DN32	PN40	425	11811995
Flange	DN50	PN40	425	11811997

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.