




Oilmeter fig. 8217 brass external thread

Characteristics

Type: 8217
Model: Olie meter
Process connection: External thread
Accuracy class: 1.0 %
Mounting: Horizontal and vertical
Pressure rating flange: PN25
Max. pressure: 16 bar
Housing material: Brass

Characteristics [2]

Material inner parts: Brass with anodized aluminium
Switching power: 50mA 48V AC/DC
Maximum medium temperature (continuous): 130 °C



Nominal inner diameter	Size process connection	Orifice	Connection size coupling	Measuring range nominal Qn m³/h	Starting volume flow l/h	Minimum volume flow l/h	Maximum volume flow m³/h	Pulse output	Contact version	Article
DN32	1.1/4" BSPP[G]	25 mm	1" [25]	2	30	75	3	1 liter/pulse	Reedcontact	12725905
DN32	1.1/4" BSPP[G]	25 mm	1" [25]	2	30	75	3			11814854
DN25	1" BSPP[G]	20 mm	3/4" [20]	1	12	40	1.5			11814849
DN25	1" BSPP[G]	20 mm	3/4" [20]	1	12	40	1.5	1 liter/pulse	Reedcontact	11814850
DN20	3/4" BSPP[G]	15 mm	1/2" [15]	0.4	4	20	0.6			11814845
DN20	3/4" BSPP[G]	15 mm	1/2" [15]	0.4	4	20	0.6	1 liter/pulse	Reedcontact	11814847

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.