




Oilmeter fig. 8217 brass flange

Characteristics

- Type:** 8217
Model: Olie meter
Accuracy class: 1.0 %
Mounting: Horizontal and vertical
Pressure rating flange: PN25
Max. pressure: 25 bar
Housing material: Ductile cast iron
Material inner parts: Brass with anodized aluminium
Switching power: 50mA 48V AC/DC
Maximum medium temperature (continuous): 130 °C



Process connection	Nominal inner diameter	Size process connection	Orifice	Measuring range nominal Qn m³/h	Starting volume flow l/h	Minimum volume flow l/h	Maximum volume flow m³/h	Pulse output	Contact version	Article
Flange	DN15	DN15	15 mm	0.4	4	20	0.6			11814846
Flange	DN15	DN15	15 mm	0.4	4	20	0.6	1 liter/pulse	Reedcontact	11814848
Flange	DN20	DN20	20 mm	1	12	40	1.5			11814851
Flange	DN20	DN20	20 mm	1	12	40	1.5	1 liter/pulse	Reedcontact	11814852
Flange	DN25	DN25	25 mm	2	30	75	3	1 liter/pulse	Reedcontact	12036176
Flange	DN25	DN25	25 mm	2	30	75	3			12036175
Flange	DN40	DN40	40 mm	6	90	225	9			12036177
Flange	DN50	DN50	50 mm	20	300	750	30			11814853

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.