



GF Transition flange Series: 700 PP, glass filled Norm: EN 1092-1/02

Characteristics

Series: 700
Norm: EN 1092-1/02
Flange type: Push-on flange
Flange standard: DIN 2501
Material: PP, glass filled
Colour: Black

Application

- Can be used in combination with a welding neck collar and a flat seal
- Suitable for butt weld fittings

Technical Information

- Connection dimensions in accordance with EN 1092/DIN 2501
- Flange bore PN10

Execution

- Mounting method in accordance with DVS 2210-1, addendum 3, and DIN 16962-12 Only use undamaged and clean products
- 1 seal per connection
- Mount the collar bushings completely parallel
- Grease the nuts and bolts
- Observe and mark the prescribed tightening sequence
- Tighten to the specified torque in five steps: Hand-tight/wrench-tight, 30%, 60%, 100%, full check [clockwise]
- Tighten the connections after pressing out

Pressure rating flange	Nominal inner diameter	External tube diameter of connection	Inner diameter of push-on flange	Pitch circle	Number of bolt holes	Diameter bolt hole	Thickness flange	Article
		mm	mm	mm		mm	mm	
PN10	DN200	200	235	295	8	22	34	11318563
PN16	DN15	20	28	65	4	14	16	11259007
PN16	DN25	32	42	85	4	14	18	11176491
PN16	DN80	90	108	160	8	18	27	11255628
PN16	DN100	110	128	180	8	18	28	11318508
PN16	DN125	125	135	180	8	18	28	11318509
PN16	DN125	140	158	210	8	18	30	11318510
PN16	DN150	160	178	240	8	22	32	11318511
PN16	DN150	180	188	240	8	22	32	11318512
PN16	DN200	225	238	295	8	22	34	11318564
PN16	DN250	250	288	350	12	22	38	11318565
PN16	DN250	280	294	350	12	22	38	11318566
PN16	DN300	315	338	400	12	22	42	11318567

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.