



GF Transition flange Series: 700 PVC-U Black Norm: EN 1092-1/02 DIN 2501

Characteristics

Series: 700
Norm: EN 1092-1/02
Flange type: Push-on flange
Flange standard: DIN 2501
Material: PVC-U
Colour: Grey

Application

- Can be used in combination with collar bushing and flat seal

Technical Information

- Connection dimensions in accordance with EN 1092/DIN 2501
- Flange bore PN10

Execution

- Mounting method in accordance with DVS 2210-1, addendum 3, and DIN 16962-12 Only use undamaged and clean products
- 1 seal per connection
- Mount the collar bushings completely parallel
- Grease the nuts and bolts
- Observe and mark the prescribed tightening sequence
- Tighten to the specified torque in five steps: Hand-tight/wrench-tight, 30%, 60%, 100%, full check [clockwise]
- Tighten the connections after pressing out

Pressure rating flange	Nominal inner diameter	External tube diameter of connection	Inner diameter of push-on flange	Pitch circle	Number of bolt holes	Diameter bolt hole	Thickness flange	Article
		mm	mm	mm		mm	mm	
PN6	DN250	250	277	350	8	22	36	11173013
PN10	DN10	16	23	60	4	14	10	10042662
PN10	DN15	20	28	65	4	14	11	10042663
PN10	DN20	25	34	75	4	14	12	10042664
PN10	DN25	32	42	85	4	14	14	10042665
PN10	DN32	40	51	100	4	18	15	10042666
PN10	DN40	50	62	110	4	18	16	10042667
PN10	DN50	63	78	125	4	18	18	10042668
PN10	DN65	75	92	145	4	18	19	10042669
PN10	DN80	90	110	160	8	18	20	10042670
PN10	DN110	110	133	180	8	18	22	10042671
PN10	DN125	125	150	210	8	18	26	10042672
PN10	DN125	140	167	210	8	18	26	10042673
PN10	DN150	160	190	240	8	22	28	10042674
PN10	DN200	200	226	295	8	22	32	10042675
PN10	DN200	225	250	295	8	22	32	10042676
PN10	DN250	280	310		12			10042677
PN10	DN300	315	348		12			10042678

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.