


Complete piston type P




Characteristics

Type: P

Principle of operation: Double acting

Max. operating pressure: 16 bar

Maximum speed: 1 m/s



Bore diameter mm	Groove diameter mm	Seal height mm	Material seal	Temperature range °C	Article
20	5.2	8	NBR	-30 / 105	14412133
25	8	12	NBR	-30 / 105	14412134
25.4	6.35	12.7	NBR	-30 / 105	14412135
26	8	12	NBR	-30 / 105	14412136
28.58	6.35	12.7	NBR	-30 / 105	14412137
31.75	6.35	14.29	NBR	-30 / 105	14412139
32	8	15	NBR	-30 / 105	14412140
34.93	6.35	14.3	NBR	-30 / 105	14412141
35	8	15	NBR	-30 / 105	14412142
36	8	15	NBR	-30 / 105	14412143
40	10	18	NBR	-30 / 105	12961720
44.45	6.35	14.28	NBR	-30 / 105	14412144
50	10	18	NBR	-30 / 105	12961721
50	16	20.5	NBR	-30 / 105	14412145
50.8	9.53	15.88	NBR	-30 / 105	14412146
57.15	9.53	15.88	NBR	-30 / 105	14412147
60	12	22	NBR	-30 / 105	12961722
60.33	9.53	15.88	NBR	-30 / 105	14412148
62	15	22	NBR	-30 / 105	14412149
63	12	22	NBR	-30 / 105	12961723
63.5	9.53	15.88	NBR	-30 / 105	14412150
69.85	9.53	19.05	NBR	-30 / 105	14412151
70	12	22	NBR	-30 / 105	14412152

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Bore diameter	Groove diameter	Seal height	Material seal	Temperature range	Article
mm	mm	mm		°C	
73.03	9.53	19.05	NBR	-30 / 105	14412153
75	12	22.5	NBR	-30 / 105	14412155
75	15	22	NBR	-30 / 105	14412154
76.2	12.7	19.05	NBR	-30 / 105	14412156
80	12	25	NBR	-30 / 105	14412158
80	16	22.5	NBR	-30 / 105	14412159
80	16	25	NBR	-30 / 105	14412157
80	20	22.5	NBR	-30 / 105	14412160
82.55	12.7	19.05	NBR	-30 / 105	14412161
82.55	22.23	19.05	NBR	-30 / 105	14412162
88.9	12.7	22.23	NBR	-30 / 105	14412163
90	12	24	NBR	-30 / 105	14412164
90	16	25	NBR	-30 / 105	14060260
95.25	12.7	22.23	NBR	-30 / 105	14412165
100	12	25	NBR	-30 / 105	14412168
100	16	25	NBR	-30 / 105	14412166
100	18	25	NBR	-30 / 105	14412170
100	20	25	NBR	-30 / 105	14412167
100	20	26	NBR	-30 / 105	14412169
101.6	12.7	22.23	NBR	-30 / 105	14412171
102	16	25	NBR	-30 / 105	14412172
107.95	12.7	22.23	NBR	-30 / 105	14412173
110	18	25	NBR	-30 / 105	14412174
114.3	19.05	22.23	NBR	-30 / 105	14412175
125	18	30	NBR	-30 / 105	14412178
125	20	26	NBR	-30 / 105	14412177
125	20	30	NBR	-30 / 105	14412176
127	19.05	25.4	NBR	-30 / 105	14412179
130	20	29	NBR	-30 / 105	14412180
140	20	30	NBR	-30 / 105	14412181
146.05	19.05	25.4	NBR	-30 / 105	14412182
150	20	30	NBR	-30 / 105	14412183
152.4	19.05	25.4	NBR	-30 / 105	14412184
160	20	30	NBR	-30 / 105	14412185
160	27	31	NBR	-30 / 105	10019146
165.1	19.05	25.4	NBR	-30 / 105	14412186
177.8	31.75	28.58	NBR	-30 / 105	14412187
180	27	31	NBR	-30 / 105	14412188
190	12	35	NBR	-30 / 105	14412190
190	20	30	NBR	-30 / 105	14412189
200	20	30	NBR	-30 / 105	14412192
200	20	35	NBR	-30 / 105	14412191
200	27	35	NBR	-30 / 105	12961719
200	30	35	NBR	-30 / 105	14412193
202.2	31.75	38.1	NBR	-30 / 105	14412194
203.2	31.75	28.58	NBR	-30 / 105	14412195
250	30	35	NBR	-30 / 105	14412196
253	44.45	41.27	NBR	-30 / 105	14412197
260	16	35	NBR	-30 / 105	14412198
300	30	35	NBR	-30 / 105	14412199
320	36	40	NBR	-30 / 105	14412200
400	40	50	NBR	-30 / 105	14412201

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.