

Compact seal type 0300



Characteristics

Type: 0300

Groove type: Closed

Max. operating pressure: 200 bar

Maximum speed: 5 m/s



Rod diameter	Groove diameter	Groove width	Material seal	Compound	Material energizer	Temperature range	Article
mm	mm	mm				°C	
4	8	2	PTFE	ER99	NBR	-30 / 100	10019991
6	10	2	PTFE	ER48	NBR	-30 / 100	11049567
8	12	2	PTFE	ER81	FKM	-10 / 180	11166145
10	14	2	PTFE	ER99	NBR	-30 / 100	10019997
12	18	2.85	PTFE	ER81	FKM	-10 / 180	11166144
12	18	2.85	PTFE	ER81	NBR	-30 / 100	10020004
16	22	2.85	PTFE	ER81	NBR	-30 / 100	10020007
18	22.9	2.2	PTFE	ER59	NBR	-30 / 100	11333525
20	27.5	3.8	PTFE	ER81	NBR	-30 / 100	10020016
20	27.5	3.8	PTFE	ER99	NBR	-30 / 100	10020095
22	33	4.2	PTFE	ER48	FKM	-10 / 180	11371390
22	33	4.2	PTFE	ER48	NBR	-30 / 100	11371389
25	32.5	3.8	PTFE	ER99	NBR	-30 / 100	10020019
30	37.5	3.8	PTFE	ER99	NBR	-30 / 100	10020021
40	52.5	5.6	PTFE	ER99	NBR	-30 / 100	11207645
42	50.5	4	PTFE	ER99	NBR	-30 / 100	12037006
45	53	4	PTFE	ER81	NBR	-30 / 100	11416830
50	62.5	5.6	PTFE	ER81	NBR	-30 / 100	10020037
50	65	6.5	PTFE	ER81	FKM	-10 / 180	11423068
60	72.5	5.6	PTFE	ER81	NBR	-30 / 100	11371110
80	92.5	5.6	PTFE	ER81	NBR	-30 / 100	10020047
110	122.5	5.6	PTFE	ER81	NBR	-30 / 100	11252049
320	344	7.5	PTFE	ER81	NBR	-30 / 100	11339747

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.