

FREUDENBERG Rotomatic type M19

Characteristics



Type: M19

Application: Rod seal

Material seal: NBR/fabric

Max. operating pressure: 400 bar

Maximum speed: 0.2 m/s



Internal diameter	Outer diameter	Groove width	Seal height	Compound	Temperature range	Article
mm	mm	mm	mm		°C	
60	72	10	9	80 NBR B246	-30 / 80	12119814
70	85	11	10	80 NBR B246	-30 / 80	11115235
80	95	11	10	80 NBR B246	-30 / 80	10018606
90	110	13	12	80 NBR B246	-30 / 80	11080259
95	112	10.8	9.8	80 NBR B246	-30 / 80	12119815
95	112	11	10	80 NBR B246	-30 / 80	12119816
100	120	13	12	80 NBR B246	-30 / 80	10018728
109	129	11	10	80 NBR B246	-30 / 80	11017232
110	130	13	12	80 NBR B246	-30 / 80	10018729
125	145	13	12	80 NBR B246	-30 / 80	10018730
130	150	10	9	80 NBR B246	-30 / 80	11121660
140	160	13	12	80 NBR B246	-30 / 80	10018731
150	170	13	12	80 NBR B246	-30 / 80	12119817
160	185	16	15	80 NBR B246	-30 / 80	12119821
180	205	16	15	80 NBR B246	-30 / 80	12119818
200	225	15	14	80 NBR B246	-30 / 80	11128811

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.