



FREUDENBERG Compact seal type S8

Characteristics

Type: S8

Max. operating pressure: 250 bar

Maximum speed: 0.5 m/s



Rod diameter	Groove diameter	Groove width	Seal height	Material seal	Compound	Temperature range	Article
mm	mm	mm	mm			°C	
5	12	6.4	6	NBR/fabric	70 NBR B209	-30 / 100	10018638
6	13	6.4	6	NBR/fabric	70 NBR B209	-30 / 100	10018639
8	15	6.4	6	NBR/fabric	70 NBR B209	-30 / 100	10018640
10	17	6.4	6	NBR/fabric	70 NBR B209	-30 / 100	10018681
12	19	6.4	6	NBR/fabric	70 NBR B209	-30 / 100	10018682
15	23	6.4	6	NBR/fabric	70 NBR B209	-30 / 100	10018683
16	24	6.4	6	NBR/fabric	70 NBR B209	-30 / 100	10018684
18	26	6.4	6	NBR/fabric	70 NBR B209	-30 / 100	10018685
20	28	6.4	6	NBR/fabric	70 NBR B209	-30 / 100	10018686
22	30	6.4	6	NBR/fabric	70 NBR B209	-30 / 100	10018687
25	32	6.3	6	NBR/fabric	70 NBR B209	-30 / 100	11094760
25	33	6.4	6	NBR/fabric	70 NBR B209	-30 / 100	10018688
28	36	6.4	6	NBR/fabric	70 NBR B209	-30 / 100	10018689
30	38	6.4	6	NBR/fabric	70 NBR B209	-30 / 100	10018690
32	40	6.4	6	NBR/fabric	70 NBR B209	-30 / 100	10018691
35	43	6.4	6	NBR/fabric	70 NBR B209	-30 / 100	10018692
36	44	6.4	6	NBR/fabric	70 NBR B209	-30 / 100	10018693
40	48	6.4	6	NBR/fabric	70 NBR B209	-30 / 100	10018694
42	50	6.4	6	NBR/fabric	70 NBR B209	-30 / 100	10018695
44	55	10.6	10	NBR/fabric	70 NBR B209	-30 / 100	11126505
45	53	8.5	8	NBR/fabric	70 NBR B209	-30 / 100	12588335
45	55	8	7.5	NBR/fabric	70 NBR B209	-30 / 100	10018575

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Rod diameter	Groove diameter	Groove width	Seal height	Material seal	Compound	Temperature range	Article
mm	mm	mm	mm			°C	
50	58	8.5	8	NBR/fabric	70 NBR B209	-30 / 100	10018747
50	60	8	7.5	NBR/fabric	70 NBR B209	-30 / 100	10018576
50	62	9.5	9	NBR/fabric	70 NBR B209	-30 / 100	10018748
55	65	8	7.5	NBR/fabric	70 NBR B209	-30 / 100	10018577
56	66	8	7.5	NBR/fabric	70 NBR B209	-30 / 100	10018578
60	70	8	7.5	NBR/fabric	70 NBR B209	-30 / 100	10018579
65	77	9.6	9	NBR/fabric	70 NBR B209	-30 / 100	10018697
70	80	7.5	7	NBR/fabric	70 NBR B209	-30 / 100	12491646
70	82	9.6	9	NBR/fabric	70 NBR B209	-30 / 100	10018698
75	87	9.6	9	NBR/fabric	70 NBR B209	-30 / 100	10018699
78	90	12.5	12	NBR/fabric	70 NBR B209	-30 / 100	11067773
80	92	9.6	9	NBR/fabric	70 NBR B209	-30 / 100	10018700
80	95	12.5	12	NBR/fabric	70 NBR B209	-30 / 100	11065351
85	97	9.6	9	NBR/fabric	70 NBR B209	-30 / 100	10018701
90	102	9.6	9	NBR/fabric	70 NBR B209	-30 / 100	10018785
90	105	12	11.3	NBR/fabric	70 NBR B209	-30 / 100	11897385
95	107	12	11.3	NBR/fabric	70 NBR B209	-30 / 100	11249699
100	110	8	7.5	NBR/fabric	70 NBR B209	-30 / 100	11288726
100	115	12	11.3	NBR/fabric	70 NBR B209	-30 / 100	10018786
105	120	12.2	11.5	NBR/fabric	70 NBR B209	-30 / 100	12270563
110	125	12	11.3	NBR/fabric	70 NBR B209	-30 / 100	10018787
115	130	12	11.3	NBR/fabric	70 NBR B209	-30 / 100	10018788
120	135	12	11.3	NBR/fabric	70 NBR B209	-30 / 100	10018750
125	140	12	11.3	NBR/fabric	70 NBR B209	-30 / 100	10018789
130	145	11	10.2	NBR/fabric	70 NBR B209	-30 / 100	10018790
135	150	11	10	NBR/fabric	70 NBR B209	-30 / 100	11032527
140	160	16	15	NBR/fabric	70 NBR B209	-30 / 100	11131828
150	170	16	15	NBR/fabric	70 NBR B209	-30 / 100	10018792
155	175	16	15	NBR/fabric	70 NBR B209	-30 / 100	12734904
160	180	16	15	NBR/fabric	70 NBR B209	-30 / 100	10018793
165	185	16	15	NBR/fabric	70 NBR B209	-30 / 100	11013585
180	200	16	15	NBR/fabric	70 NBR B209	-30 / 100	10018794
200	220	16	15	NBR/fabric	70 NBR B209	-30 / 100	11295888

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.