

FREUDENBERG U-cup type AUN1


Characteristics

Type: AUN100

Material seal: PUR

Max. operating pressure: 200 bar

Maximum speed: 0.5 m/s



Internal diameter	Outer diameter	Groove width	Seal height	Compound	Temperature range	Article
mm	mm	mm	mm		°C	
4	10	4.7	4	94 AU 925	-30 / 110	11292987
6	12	7	6	94 AU 925	-30 / 110	11292985
8	14	7	6	94 AU 925	-30 / 110	11348306
8	16	7	6	94 AU 925	-30 / 110	11292984
8	25	7	6	94 AU 925	-30 / 110	11878910
10	16	7	6	94 AU 925	-30 / 110	11292983
10	18	9	8	94 AU 925	-30 / 110	11318753
10	20	9	8	94 AU 925	-30 / 110	11292982
10	22	7	6	94 AU 925	-30 / 110	11457507
12	18	7	6	94 AU 925	-30 / 110	11318139
12	20	9	8	94 AU 925	-30 / 110	11094939
12	22	6	5	94 AU 925	-30 / 110	11950539
12	24	10	9	94 AU 925	-30 / 110	11457508
14	22	7	6	94 AU 925	-30 / 110	11328740
14	22	9	8	94 AU 925	-30 / 110	11950541
15	25	9	8	94 AU 925	-30 / 110	11292981
18	32	8	7	94 AU 925	-30 / 110	11950553
20	26	6	5	94 AU 925	-30 / 110	11878923
20	28	9	8	94 AU 925	-30 / 110	11330874
20	30	9	8	94 AU 925	-30 / 110	11292978
20	36	9	8	94 AU 925	-30 / 110	11292977
24	32	8	7	94 AU 925	-30 / 110	11292975
24	40	9	8	94 AU 925	-30 / 110	11447665

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Internal diameter	Outer diameter	Groove width	Seal height	Compound	Temperature range	Article
mm	mm	mm	mm		°C	
25	35	6	5	94 AU 925	-30 / 110	11229217
28	38	9	8	94 AU 925	-30 / 110	11292973
30	37	9	8	94 AU 925	-30 / 110	11950559
30	40	6	5	94 AU 925	-30 / 110	11292971
30	45	11	10	94 AU 925	-30 / 110	11950560
30	50	11	10	94 AU 925	-30 / 110	11292972
35	45	9	8	94 AU 925	-30 / 110	11292970
35	55	11	10	94 AU 925	-30 / 110	11318140
38	50	10	9	94 AU 925	-30 / 110	11292969
40	48	12	11	94 AU 925	-30 / 110	11292906
40	50	9	8	94 AU 925	-30 / 110	11292966
40	65	13	12	94 AU 925	-30 / 110	11950565
40	70	16	15	94 AU 925	-30 / 110	11878924
45	65	11	10	94 AU 925	-30 / 110	11292965
48	60	10	9	94 AU 925	-30 / 110	11950566
50	70	11	10	94 AU 925	-30 / 110	11292964
52	70	10	9	94 AU 925	-30 / 110	11950567
55	75	11	10	94 AU 925	-30 / 110	11878914
60	80	19	18	94 AU 925	-30 / 110	11335402
180	200	19	18	94 AU 925	-30 / 110	11020464
290	320	21	20	94 AU 925	-30 / 110	11117389

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.