

HALLITE Compact seal type 18





Characteristics

Type: 18

Material seal: NBR/fabric

Max. operating pressure: 500 bar

Maximum speed: 0.5 m/s



Internal diameter	Outer diameter	Groove width	Temperature range	Article
mm	mm	mm	°C	
25	40	11	-30 / 100	12092473
30	38	8	-30 / 100	12317251
30	45	11	-30 / 100	12092374
30	50	14	-30 / 100	12092376
35	50	11	-30 / 100	12092460
40	50	10.5	-30 / 100	12045397
40	50	10.5	-30 / 100	12092438
40	50	13	-30 / 100	12092439
40	55	11	-30 / 100	12092464
40	60	14	-30 / 100	12092440
45	53	8	-30 / 100	12092441
50	60	7.5	-30 / 100	12092457
50	65	11	-30 / 100	12092442
50	70	14	-30 / 100	12702726
55	65	14	-30 / 100	12092443
57.15	82.55	19.05	-30 / 100	12445924
60	71	9	-30 / 100	12092444
60	72	9.5	-30 / 100	12092445
60	80	14	-30 / 100	12092446
63	83	14	-30 / 100	12092447
63.5	82.55	14.28	-30 / 100	13011740
63.5	88.9	15.9	-30 / 100	12092455
69.85	88.9	14.28	-30 / 100	12115442

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Internal diameter	Outer diameter	Groove width	Temperature range	Article
mm	mm	mm	°C	
70	78	6	-30 / 100	12317188
70	90	14	-30 / 100	12092448
75	95	14	-30 / 100	12356605
80	95	12	-30 / 100	12092449
80	100	14	-30 / 100	12092450
90	110	14	-30 / 100	12092466
90	110	15	-30 / 100	12317189
100	120	14	-30 / 100	12092463
100	120	15	-30 / 100	12310000
100	125	19	-30 / 100	12356604
110	130	14	-30 / 100	12092451
125	150	19	-30 / 100	12092458
139.7	165.1	19.05	-30 / 100	11603216
140	160	14	-30 / 100	12092452
150	170	14	-30 / 100	12092469
160	180	15	-30 / 100	12092453
160	190	23	-30 / 100	12092467
175	200	19	-30 / 100	11023739
180	200	15	-30 / 100	12092471
200	220	15	-30 / 100	11752496
200	220	15	-30 / 100	12092462
200	247.7	38.5	-30 / 100	11201292
220	250	22	-30 / 100	12092489
220	250	31	-30 / 100	12092491
240	260	17	-30 / 100	12478611
250	280	24	-30 / 100	12092490
280	310	24	-30 / 100	12092454
320	360	30	-30 / 100	12092470
360	400	30	-30 / 100	12092472
377	410	30	-30 / 100	12092468
400	440	30	-30 / 100	14337253
430	500	31	-30 / 100	12386642
440	480	30	-30 / 100	12941804

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.