


FREUDENBERG Chevron set type ESV

Characteristics

Type: ESV

Max. operating pressure: 400 bar

Maximum speed: 0.5 m/s



Rod diameter	Groove diameter	Groove width	Material seal	Compound	Temperature range	Article
mm	mm	mm			°C	
20	30	18.5	FKM/fabric	BI-FKM B3K674	-15 / 140	11077108
45	60	22.5	FKM/fabric	BI-FKM B3K674	-15 / 140	11294121
50	65	22.5	FKM/fabric	BI-FKM B3K674	-15 / 140	11032315
56	71	22.5	FKM/fabric	BI-FKM B3K674	-15 / 140	11292863
70	85	22.5	FKM/fabric	BI-FKM B3K674	-15 / 140	11315154
80	95	22.5	FKM/fabric	BI-FKM B3K674	-15 / 140	11246203
90	110	40	FKM/fabric	BI-FKM B3K674	-15 / 140	11382926
100	115	30	FKM/fabric	BI-FKM B3K674	-15 / 140	11382928
140	155	34	FKM/fabric	BI-FKM B3K674	-15 / 140	12719250
180	210	60	FKM/fabric	BI-FKM B4K674	-15 / 140	11608086
420	460	55	FKM/fabric	BI-FKM B4K674	-15 / 140	11276635

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.