


FREUDENBERG Spring activated seal type FOI

Characteristics

Type: FOI

Max. operating pressure: 300 bar

Maximum speed: 15 m/s



Rod diameter	Groove diameter	Groove width	Seal height	Material seal	Compound	Temperature range	Article
mm	mm	mm	mm			°C	
6	8.9	2.4	2.1	PTFE	PTFE F56110	-200 / 260	12313619
8	10.9	2.4	2.1	PTFE	PTFE F56110	-200 / 260	11361835
10	12.9	2.4	2.1	PTFE	PTFE F56110	-200 / 260	12313620
16	20.5	3.6	3.2	PTFE	PTFE F56110	-200 / 260	11338546
18	22.5	3.6	3.2	PTFE	PTFE F56110	-200 / 260	11315886
20	24.5	3.6	3.2	PTFE	PTFE F56110	-200 / 260	11338547
22	28.2	4.8	4.3	PTFE	PTFE F56110	-200 / 260	11346834
28	34.2	4.8	4.3	PTFE	PTFE F56110	-200 / 260	12313633
30	36.2	4.8	4.3	PTFE	PTFE F56110	-200 / 260	12058682
32	38.2	4.8	4.3	PTFE	PTFE F56110	-200 / 260	12313635
40	46.2	4.8	4.3	PTFE	PTFE F56110	-200 / 260	11458934
50	59.4	7.1	6.6	PTFE	PTFE F56110	-200 / 260	11309103
							12508860

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.