



ERIKS Guide ring type EPGU

Characteristics

Type: EPGU

Material: POM

Temperature range: -40 / 110 °C

Internal diameter	Outer diameter	Width	Groove width	Thickness	Article
mm	mm	mm	mm	mm	
20	25	5.6	5.6	2.5	11655913
30	26	9.6	9.6	3	11049192
31	35	8	8	2	10019699
34	40	9.6	10	3	11093025
36	40	8	8	2	11108478
39	45	9.6	9.6	3	12961534
44	50	9.6	9.6	3	10019700
46	50	9.6	10	2	11108117
49	55	12.8	12.8	3	10019701
54	60	9.6	9.6	3	11154726
54	60	12.8	12.8	3	10019702
56	60	10	10	2	11110290
59	65	12.8	12.8	3	10019703
63	57	9.6	9.6	3	11037029
64	70	12.8	12.8	3	10019704
69	75	12.8	12.8	3	12961535
74	80	12.7	12.7	3	11108479
74	80	12.8	12.8	3	10019705
79	85	12.8	12.8	3	12961536
84	90	12.8	12.8	3	10019706
89	95	12.7	12.7	3	11382776
94	100	12.8	12.8	3	10019707
104	110	12.8	12.8	3	10019709
114	120	12.8	12.8	3	10019710
119	125	12.8	12.8	3	10019711
134	140	12.8	12.7	3	10019713
144	150	12.8	12.7	3	10019714
154	160	19.2	19.2	3	10019715
174	180	19.2	19.2	3	10019716
194	200	19.2	19.2	3	10019717
214	220	19.2	19.2	3	10019718
244	250	19.2	19.2	3	10019719
254	260	19.2	19.2	3	11443758
274	280	19.2	19.2	3	11370945
274	280	19.2	19.2	3	10019720

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.