



ERIKS Guide strip type Powerslide T100G

Characteristics

Type: Powerslide

Material: T100G

Temperature range: -40 / 100 °C

Internal diameter	Outer diameter	Width	Groove width	Thickness	Article
mm	mm	mm	mm	mm	
50	80	9.5	9.7	2.5	12474221
55	85	9.5	9.7	2.5	12474222
60	90	9.5	9.7	2.5	12474383
65	95	9.5	9.7	2.5	12474384
70	100	9.5	9.7	2.5	12474385
75	80	9.5	9.7	2.5	12474386
80	390	9.5	9.7	2.5	12474387
85	90	9.5	9.7	2.5	12474388
90	95	9.5	9.7	2.5	12379908
95	100	9.5	9.7	2.5	12474389
100	105	14.8	15	2.5	12354669
100	130	9.5	9.7	2.5	12354638
105	110	14.8	15	2.5	12354670
105	130	9.5	9.7	2.5	12354639
110	115	14.8	15	2.5	12354671
110	135	9.5	9.7	2.5	12354640
115	120	14.8	15	2.5	12354672
115	140	9.5	9.7	2.5	12354641
120	125	14.8	15	2.5	12354673
120	145	9.5	9.7	2.5	12354642
125	130	14.8	15	2.5	12354674
125	150	9.5	9.7	2.5	12342278
125	155	9.5	9.7	2.5	12354643
130	135	14.8	15	2.5	12354675
130	160	9.5	9.7	2.5	12354644
135	140	14.8	15	2.5	12354676
135	165	9.5	9.7	2.5	12354645
140	145	14.8	15	2.5	12354677
140	170	9.5	9.7	2.5	12354646
145	150	14.8	15	2.5	12354678
145	175	9.5	9.7	2.5	12354647
150	155	14.8	15	2.5	12354679
150	155	24.5	25	2.5	12354710
150	180	9.5	9.7	2.5	12354648
155	160	14.8	15	2.5	12354680
155	160	24.5	25	2.5	12354711
155	185	9.5	9.7	2.5	12354649
160	165	14.8	15	2.5	12354681
160	165	24.5	25	2.5	12354712
160	190	9.5	9.7	2.5	12354650
165	170	14.8	15	2.5	12354682
165	170	24.5	25	2.5	12354713
165	195	9.5	9.7	2.5	12354651

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Internal diameter	Outer diameter	Width	Groove width	Thickness	Article
mm	mm	mm	mm	mm	
170	175	14.8	15	2.5	12354683
170	175	24.5	25	2.5	12354714
170	200	9.5	9.7	2.5	12354652
175	180	14.8	15	2.5	12354684
175	180	24.5	25	2.5	12354715
175	205	9.5	9.7	2.5	12354653
180	185	14.8	15	2.5	12354685
180	185	24.5	25	2.5	12354716
180	210	9.5	9.7	2.5	12354654
185	190	14.8	15	2.5	12354686
185	190	24.5	25	2.5	12354717
185	215	9.5	9.7	2.5	12354655
190	195	14.8	15	2.5	12354687
190	195	24.5	25	2.5	12354718
190	220	9.5	9.7	2.5	12354656
195	200	14.8	15	2.5	12354688
195	200	24.5	25	2.5	12354719
195	225	9.5	9.7	2.5	12354657
200	205	14.8	15	2.5	12354689
200	205	24.5	25	2.5	12354720
200	230	9.5	9.7	2.5	12354658
205	210	14.8	15	2.5	12354690
205	210	24.5	25	2.5	12354721
205	235	9.5	9.7	2.5	12354659
210	215	14.8	15	2.5	12354691
210	215	24.5	25	2.5	12354722
210	240	9.5	9.7	2.5	12354660
215	220	14.8	15	2.5	12354692
215	220	24.5	25	2.5	12354723
215	245	9.5	9.7	2.5	12354661
220	225	14.8	15	2.5	12354693
220	225	24.5	25	2.5	12354724
220	250	9.5	9.7	2.5	12354662
225	230	14.8	15	2.5	12354694
225	230	24.5	25	2.5	12354725
225	255	9.5	9.7	2.5	12354663
230	55	9.5	9.7	2.5	12354664
230	235	14.8	15	2.5	12354695
230	235	24.5	25	2.5	12354726
235	60	9.5	9.7	2.5	12354665
235	240	14.8	15	2.5	12354696
235	240	24.5	25	2.5	12354727
240	65	9.5	9.7	2.5	12354666
240	245	14.8	15	2.5	12354697
240	245	24.5	25	2.5	12354728
245	70	9.5	9.7	2.5	12354667
245	250	14.8	15	2.5	12354698
245	250	24.5	25	2.5	12354729
250	75	9.5	9.7	2.5	12354668
250	255	14.8	15	2.5	12354699
250	255	24.5	25	2.5	12354730
255	260	14.8	15	2.5	12354700
255	260	24.5	25	2.5	12354731

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Internal diameter	Outer diameter	Width	Groove width	Thickness	Article
mm	mm	mm	mm	mm	
260	265	14.8	15	2.5	12354701
260	265	24.5	25	2.5	12354732
265	270	14.8	15	2.5	12354702
265	270	24.5	25	2.5	12354733
270	275	14.8	15	2.5	12354703
270	275	24.5	25	2.5	12354734
275	280	14.8	15	2.5	12354704
275	280	24.5	25	2.5	12354735
280	285	14.8	15	2.5	12354705
280	285	24.5	25	2.5	12354736
285	290	14.8	15	2.5	12354706
285	290	24.5	25	2.5	12354737
290	295	14.8	15	2.5	12354707
290	295	24.5	25	2.5	12354738
295	300	14.8	15	2.5	12354708
295	300	24.5	25	2.5	12354739
300	305	14.8	15	2.5	12354709
300	305	24.5	25	2.5	12354740
305	310	24.5	25	2.5	12354741
310	315	24.5	25	2.5	12354742
315	320	24.5	25	2.5	12354743
320	325	24.5	25	2.5	12354744
325	330	24.5	25	2.5	12354745
330	335	24.5	25	2.5	12354746
335	340	24.5	25	2.5	12354747
340	345	24.5	25	2.5	12354748
345	350	24.5	25	2.5	12354749
350	355	24.5	25	2.5	12354750
355	360	24.5	25	2.5	12354751
360	365	24.5	25	2.5	12354752
365	370	24.5	25	2.5	12354753
370	375	24.5	25	2.5	12354754
375	380	24.5	25	2.5	12354755
380	385	24.5	25	2.5	12354756
385	390	24.5	25	2.5	12354757
390	395	24.5	25	2.5	12354758
395	400	24.5	25	2.5	12354759
400	405	24.5	25	2.5	12354760
		5.5	5.6	2.5	10019771
		6.1	6.2	2.5	10019766
		9.5	9.7	2.5	10019772
		14.8	15	2.5	10019773
		19.5	20	2.5	10019769
		24.5	25	2.5	10019774
		24.5	25	4	11544487
		24.5	25	4	12217939

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.