



ERIKS Rubber flange gasket NR 65 BLANCA EN 1514-1 IBC

Characteristics

Series: NR 65

Type: BLANCA

Compound: 130101

Norm: EN 1514-1 IBC

Hardness (Sh A): 65 Sh A

Colour: White

Temperature range: -45 / 80 °C

Max. pressure: 10 bar

Suitable for medium: Air [compressed air], Water,
Food & Beverages, Water [process water]

Application

- Recommended in: Food & Beverages

Number of inserts	Nominal diameter	Flange pressure stage	Outer diameter	Inner diameter	Thickness	Flange standard	Article
			mm	mm	mm		
0	DN15	PN10/40	51	22	3	EN 1092-1 RF	11148976
0	DN20	PN10/40	61	27	3	EN 1092-1 RF	11148975
0	DN25	PN10/40	71	34	3	EN 1092-1 RF	11148973
0	DN32	PN10/40	82	43	3	EN 1092-1 RF	11148979
0	DN40	PN10/40	92	49	3	EN 1092-1 RF	11148980
0	DN50	PN10/40	107	61	3	EN 1092-1 RF	11148981
0	DN65	PN10/40	127	77	3	EN 1092-1 RF	11148982
0	DN80	PN10/40	142	89	3	EN 1092-1 RF	11149003
0	DN100	PN10/16	162	115	3	EN 1092-1 RF	11149004
0	DN125	PN10/16	192	141	3	EN 1092-1 RF	11149005
0	DN200	PN10/16	273	220	3	EN 1092-1 RF	12158573
0	DN250	PN10	328	273	3	EN 1092-1 RF	12268759
0	DN350	PN10	438	356	3	EN 1092-1 RF	12158525
0	DN400	PN10	489	407	3	EN 1092-1 RF	12268761
0	DN600	PN10	695	610	3	EN 1092-1 RF	12268763

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.