


FRENZELIT Fibre flange gasket NOVAPRESS 815 EN 1514-1 IBC



Characteristics

Series: NOVAPRESS
Type: 815
Norm: EN 1514-1 IBC
With Inner eyelet: No
Fibre type: Aramid
Anti sticking layer: Yes
Temperature range: -50 / 150 °C
Max. pressure: 50 bar

Characteristics [2]

Suitable for medium: Weak Acids, Solvents, Fuels, Natural gas, Lubricant, Weak Alkalis, Refrigerants, Grease, Oil, Air [compressed air], Biodiesel
Approval according to: DVGW, GL, DVGW W270

Nominal diameter	Flange pressure stage	Outer diameter mm	Inner diameter mm	Thickness mm	Article
DN10	PN10/40	46	18	2	11088182
DN15	PN10/40	51	22	2	10002894
DN20	PN10/40	61	27	1.5	11914496
DN20	PN10/40	61	27	2	10002895
DN25	PN10/40	71	34	2	10002896
DN32	PN10/40	82	43	2	10002897
DN40	PN10/40	92	49	2	10002898
DN50	PN10/40	107	61	2	10002899
DN65	PN10/40	127	77	2	10002900
DN80	PN10/40	142	89	2	10002901
DN100	PN25/40	168	115	2	11044115
DN100	PN10/16	162	115	2	10002890
DN125	PN25/40	194	141	2	11044116
DN125	PN10/16	192	141	2	10002891
DN150	PN25/40	224	169	2	11044117
DN150	PN10/16	218	169	2	10002892
DN200	PN10/16	273	220	2	10002893
DN200	PN25	284	220	2	11044118
DN200	PN40	290	220	2	11044130
DN250	PN25	340	273	2	11044132
DN250	PN16	329	273	2	11044131
DN250	PN10	328	273	2	10002889
DN250	PN40	352	273	2	11044133
DN300	PN10	378	324	2	11127981
DN300	PN16	384	324	2	11044135
DN300	PN40	417	324	2	11044137
DN300	PN25	400	324	2	11044136
DN350	PN25	457	356	2	11044151
DN350	PN10	438	356	2	11044138
DN350	PN40	474	356	2	11044152
DN350	PN16	444	356	2	11044139
DN400	PN25	514	407	2	11044155
DN400	PN16	495	407	2	11044154
DN400	PN10	489	407	2	11044153
DN400	PN40	546	407	2	11044156
DN500	PN40	628	508	2	11044172
DN500	PN16	617	508	2	11044170
DN500	PN25	624	508	2	11044171
DN500	PN10	594	508	2	11044159

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal diameter	Flange pressure stage	Outer diameter	Inner diameter	Thickness	Article
		mm	mm	mm	
DN600	PN16	734	610	2	11044174
DN600	PN40	747	610	2	11044177
DN600	PN10	695	610	2	11044173
DN600	PN25	734	610	2	11044176

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.