



LEADER Fibre flange gasket FYBAR PT50 EN 1514-1 IBC

Characteristics

Series: FYBAR
Type: PT50
Norm: EN 1514-1 IBC
With Inner eyelet: No
Fibre type: Aramid
Anti sticking layer: Yes
Temperature range: -30 / 200 °C
Max. pressure: 85 bar

Characteristics [2]

Suitable for medium: Fuels, Grease, Potable water, Weak Alkalis, Chlorine Water < 5% [7782-50-5], Chlorine, gaseous [7782-50-5], Oil, Weak Acids, Refrigerants, Air [compressed air], Solvents, Biodiesel, Natural gas, Lubricant
Approval according to: BS7531 Grade Y, UBA Elastomerleitlinie, GL, TA-Luft, Blow out VDI2200, DVGW, DVGW W270, HTB DIN30653

Nominal diameter	Flange pressure stage	Outer diameter mm	Inner diameter mm	Thickness mm	Article
DN10	PN10/40	46	18	2	10002931
DN15	PN10/40	51	22	2	10002932
DN20	PN10/40	61	27	2	10002933
DN25	PN10/40	71	34	2	10002934
DN32	PN10/40	82	43	2	10002935
DN40	PN10/40	92	49	2	10002936
DN50	PN10/40	107	61	2	10002937
DN65	PN10/40	127	77	2	10002938
DN80	PN10/40	142	89	2	10002939
DN100	PN10/16	162	115	2	10002927
DN100	PN25/40	168	115	2	11043637
DN125	PN10/16	192	141	2	10002928
DN125	PN25/40	194	141	2	11043638
DN150	PN10/16	218	169	2	10002929
DN150	PN25/40	224	169	2	11043639
DN200	PN10/16	273	220	2	10002930
DN200	PN25	284	220	2	11043650
DN200	PN40	290	220	2	11043651
DN250	PN16	329	273	2	11043652
DN250	PN10	328	273	2	10002921
DN250	PN25	340	273	2	11043653
DN250	PN40	352	273	2	11043654
DN300	PN16	384	324	2	11043656
DN300	PN10	378	324	2	10002922
DN300	PN25	400	324	2	11043657
DN300	PN40	417	324	2	11043658
DN350	PN10	438	356	2	10002923
DN350	PN16	444	356	2	11043659
DN350	PN25	457	356	2	11043670
DN350	PN40	474	356	2	11043671
DN400	PN16	495	407	2	11043672
DN400	PN10	489	407	2	10002924
DN400	PN25	514	407	2	11043673
DN400	PN40	546	407	2	11043674
DN500	PN25	624	508	2	11043676
DN500	PN16	617	508	2	11043675
DN500	PN10	594	508	2	10002925
DN500	PN40	628	508	2	11043677
DN600	PN16	734	610	2	11043679

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal diameter	Flange pressure stage	Outer diameter	Inner diameter	Thickness	Article
		mm	mm	mm	
DN600	PN10	695	610	2	10002926
DN600	PN25	731	610	2	11043680
DN600	PN40	747	610	2	11043681

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.