



LEADER Fibre flange gasket FYBAR PT60 EN 1514-1 IBC

Characteristics

Series: FYBAR
Type: PT60
Norm: EN 1514-1 IBC
With inner eyelet: No
Fibre type: Aramid, Glass
Anti sticking layer: Yes
Temperature range: -30 / 250 °C
Max. pressure: 100 bar

Characteristics [2]

Suitable for medium: Natural gas, Chlorine, gaseous [7782-50-5], Air (compressed air), Chlorine Water < 5% [7782-50-5], Oil, Solvents, Refrigerants, Potable water, Fuels, Weak Acids, Biodiesel, Lubricant, Grease, Weak Alkalis
Approval according to: DVGW, WRAS, TA-Luft, BS7531 Grade X, DVGW W270, BAM

Nominal diameter	Flange pressure stage	Outer diameter mm	Inner diameter mm	Thickness mm	Article
DN10	PN10/40	46	18	2	11935987
DN15	PN10/40	51	22	2	11935988
DN20	PN10/40	61	27	2	11935989
DN25	PN10/40	71	34	2	11935990
DN32	PN10/40	82	43	2	11935991
DN40	PN10/40	92	49	2	11935992
DN50	PN10/40	107	61	2	11935993
DN65	PN10/40	127	77	2	11935994
DN80	PN10/40	142	89	2	11935995
DN100	PN10/16	162	115	2	11935983
DN100	PN25/40	168	115	2	12259743
DN125	PN10/16	192	141	2	11935984
DN125	PN25/40	194	141	2	12259744
DN150	PN10/16	218	169	2	11935985
DN150	PN25/40	224	169	2	12259745
DN200	PN40	290	220	2	12259754
DN200	PN25	284	220	2	12259746
DN200	PN10/16	273	220	2	11935986
DN250	PN25	340	273	2	12259747
DN250	PN16	329	273	2	12259736
DN250	PN40	352	273	2	12259755
DN250	PN10	328	273	2	11935947
DN300	PN10	378	324	2	11935948
DN300	PN25	400	324	2	12259748
DN300	PN16	384	324	2	12259737
DN300	PN40	417	324	2	12259756
DN350	PN25	457	356	2	12259749
DN350	PN16	444	356	2	12259738
DN350	PN40	474	356	2	12259757
DN350	PN10	438	356	2	11935949
DN400	PN16	495	407	2	12259739
DN400	PN10	489	407	2	11935950
DN400	PN25	514	407	2	12259750
DN400	PN40	546	407	2	12259758
DN500	PN40	628	508	2	12259760
DN500	PN10	594	508	2	11935951
DN500	PN25	624	508	2	12259752
DN500	PN16	617	508	2	12259741
DN600	PN16	734	610	2	12259742

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal diameter	Flange pressure stage	Outer diameter	Inner diameter	Thickness	Article
		mm	mm	mm	
DN600	PN10	695	610	2	11935952
DN600	PN40	747	610	2	12259761
DN600	PN25	731	610	2	12259753

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.