

REINZ Fibre flange gasket AFM 34 EN 1514-1 IBC



Characteristics

Series: AFM

Type: 34

Norm: EN 29454.1, 3.1.1.A [F-SW 12]

With Inner eyelet: No

Fibre type: Aramid

Anti sticking layer: Yes

Temperature range: -50 / 250 °C

Max. pressure: 150 bar

Characteristics [2]

Suitable for medium: Chlorine Water < 5% [7782-50-5], Lubricant, Food & Beverages, Solvents, Potable water, Chlorine, gaseous [7782-50-5], Fuels, Oil, Natural gas, Grease, Low pressure steam, Air [compressed air]

Approval according to: BS7531 Grade X, BS6755, GL, HTB DIN30653, TA-Luft, DVGW, BAM, API 6FB

Nominal diameter	Flange pressure stage	Outer diameter mm	Inner diameter mm	Thickness mm	Article
DN10	PN10/40	46	18	2	12754372
DN15	PN10/40	51	22	2	11129073
DN20	PN10/40	61	27	2	11129074
DN25	PN10/40	71	34	2	11129075
DN32	PN10/40	82	43	2	11129076
DN40	PN10/40	92	49	2	11129077
DN50	PN10/40	107	61	2	11129079
DN65	PN10/40	127	77	2	11129080
DN80	PN10/40	142	89	2	11129082
DN100	PN10/16	162	115	2	11129083
DN100	PN25/40	168	115	2	11324258
DN125	PN25/40	194	141	2	11324259
DN125	PN10/16	192	141	2	11129084
DN150	PN10/16	218	169	2	11129085
DN150	PN25/40	224	169	2	11324264
DN200	PN40	290	220	2	11324269
DN200	PN25	284	220	2	11324268
DN200	PN10/16	273	220	2	11129086
DN250	PN25	340	273	2	11324375
DN250	PN16	329	273	2	11324374
DN250	PN10	328	273	2	11129087
DN250	PN40	352	273	2	12754376
DN300	PN16	384	324	2	11442268
DN300	PN40	417	324	2	12754377
DN300	PN25	400	324	2	11324377
DN300	PN10	378	324	2	11180065
DN350	PN40	474	356	2	11816174
DN350	PN10	438	356	2	11129091
DN350	PN16	444	356	2	12754373
DN350	PN25	457	356	2	12764356
DN400	PN25	514	407	2	12754375
DN400	PN40	546	407	2	12754378
DN400	PN16	495	407	2	11816168

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal diameter	Flange pressure stage	Outer diameter	Inner diameter	Thickness	Article
		mm	mm	mm	
DN400	PN10	489	407	2	11129093
DN500	PN25	624	508	2	11324404
DN500	PN40	628	508	2	11324405
DN500	PN16	617	508	2	12703855
DN500	PN10	594	508	2	11180097
DN600	PN25	734	610	2	11324407
DN600	PN40	747	610	2	12754379
DN600	PN16	734	610	2	12754374
DN600	PN10	695	610	2	11129097

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.