


LEADER PTFE flange gasket CLIPPERLON 2110 ASME B16.21

**Characteristics****Series:** CLIPPERLON**Type:** 2110**Norm:** ASME B16.21**Material structure:** PTFE, modified**Marking:** Printed**Temperature range:** -210 / 240 °C**Max. pressure:** 40 bar

Suitable for medium: Air (compressed air), Food & Beverages, Low pressure steam, Solvents, Weak Acids, Hydrocarbons, Cryogenic, Acids, Chlorine, gaseous (7782-50-5), Refrigerants, Weak Alkalis, Alkalis, Potable water, Fuels, Chlorine Water < 5% (7782-50-5)

Approval according to: FDA 21 CFR 177.1550, Blow out VDI2200, EC1935 (10/2011), WRAS, TA-Luft

Application

- Recommended in: Chemical, Food & Beverages

Nominal diameter	Flange pressure stage	Outer diameter mm	Inner diameter mm	Thickness mm	Article
1/2"	150lbs	48	21	1.5	11934202
1/2"	300/600lbs	54	21	1.5	11934229
1/2"	150lbs	48	21	2	12257599
1/2"	300/600lbs	54	21	2	12257618
1/2"	150lbs	48	21	3	12257693
1/2"	300/600lbs	54	21	3	12257707
3/4"	150lbs	57	27	1.5	11934203
3/4"	300/600lbs	67	27	1.5	11934216
3/4"	300/600lbs	67	27	2	12257619
3/4"	300/600lbs	67	27	3	12257708
3/4"	150lbs	57	27	3	12257694
1"	300/600lbs	73	33	1.5	11934228
1"	150lbs	67	33	1.5	11934201
1"	300/600lbs	73	33	2	12257620
1"	150lbs	67	33	2	12257601
1"	300/600lbs	73	33	3	12257709
1"	150lbs	67	33	3	12257695
1.1/4"	150lbs	76	42	1.5	11934233
1.1/4"	300/600lbs	83	42	1.5	11934235
1.1/4"	150lbs	76	42	2	12257602
1.1/4"	300/600lbs	83	42	2	12257621
1.1/4"	300/600lbs	83	42	3	12257710
1.1/4"	150lbs	76	42	3	12257696
1.1/2"	300/600lbs	95	48	1.5	11934226
1.1/2"	150lbs	86	48	1.5	11934204
1.1/2"	300/600lbs	95	48	2	12257622
1.1/2"	150lbs	86	48	2	12257603
1.1/2"	300/600lbs	95	48	3	12257711
1.1/2"	150lbs	86	48	3	12257697
2"	300/600lbs	111	60	1.5	11934208
2"	150lbs	105	60	1.5	11934214
2"	300/600lbs	111	60	2	12257623
2"	150lbs	105	60	2	12257604
2"	300/600lbs	111	60	3	12257712
2"	150lbs	105	60	3	12257698
2.1/2"	150lbs	124	73	1.5	12257569
2.1/2"	300/600lbs	130	73	1.5	12949957

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal diameter	Flange pressure stage	Outer diameter	Inner diameter	Thickness	Article
		mm	mm	mm	
2.1/2"	300/600lbs	130	73	2	12257624
2.1/2"	150lbs	124	73	2	12257605
2.1/2"	150lbs	124	73	3	12257699
2.1/2"	300/600lbs	130	73	3	12257713
3"	300/600lbs	149	89	1.5	11934209
3"	150lbs	137	89	1.5	11934230
3"	300/600lbs	149	89	2	12257625
3"	150lbs	137	89	2	12257606
3"	300/600lbs	149	89	3	12257714
3"	150lbs	137	89	3	12257700
4"	600lbs	194	114	1.5	12257571
4"	300lbs	181	114	1.5	11934210
4"	150lbs	175	114	1.5	11934206
4"	600lbs	194	114	2	12257637
4"	300lbs	181	114	2	12257626
4"	150lbs	175	114	2	12257607
4"	300lbs	181	114	3	12257715
4"	600lbs	194	114	3	12257726
4"	150lbs	175	114	3	12257701
5"	600lbs	241	141	1.5	12257572
5"	300lbs	216	141	1.5	11934236
5"	150lbs	197	141	1.5	11934234
5"	150lbs	197	141	2	12257608
5"	600lbs	241	141	2	12257638
5"	300lbs	216	141	2	12257627
5"	150lbs	197	141	3	12257702
5"	600lbs	241	141	3	12257727
5"	300lbs	216	141	3	12257716
6"	600lbs	267	168	1.5	12257573
6"	150lbs	222	168	1.5	11934221
6"	300lbs	251	168	1.5	11934211
6"	300lbs	251	168	2	12257628
6"	600lbs	267	168	2	12257639
6"	150lbs	222	168	2	12257609
6"	600lbs	267	168	3	12257728
6"	150lbs	222	168	3	12257703
6"	300lbs	251	168	3	12257717
8"	600lbs	321	219	1.5	12257574
8"	300lbs	308	219	1.5	11934212
8"	150lbs	279	219	1.5	11934222
8"	600lbs	321	219	2	12257640
8"	300lbs	308	219	2	12257629
8"	150lbs	279	219	2	12257610
8"	600lbs	321	219	3	12257729
8"	300lbs	308	219	3	12257718
8"	150lbs	279	219	3	12134507
10"	600lbs	400	273	1.5	12257575
10"	150lbs	340	273	1.5	11934223
10"	300lbs	362	273	1.5	11934213
10"	150lbs	340	273	2	12257611
10"	300lbs	362	273	2	12257630
10"	600lbs	400	273	2	12257641
10"	300lbs	362	273	3	12257719

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal diameter	Flange pressure stage	Outer diameter	Inner diameter	Thickness	Article
		mm	mm	mm	
10"	600lbs	400	273	3	12257730
10"	150lbs	340	273	3	12134546
12"	300lbs	422	324	1.5	11934218
12"	150lbs	410	324	1.5	11934224
12"	600lbs	457	324	1.5	12257576
12"	150lbs	410	324	2	12257612
12"	300lbs	422	324	2	12257631
12"	600lbs	457	324	2	12257642
12"	150lbs	410	324	3	12134511
12"	600lbs	457	324	3	12257731
12"	300lbs	422	324	3	12257720
14"	600lbs	492	356	1.5	12257577
14"	150lbs	451	356	1.5	11934225
14"	300lbs	486	356	1.5	11934215
14"	150lbs	451	356	2	12257613
14"	300lbs	486	356	2	12257632
14"	600lbs	492	356	2	12257643
14"	600lbs	492	356	3	12257732
14"	150lbs	451	356	3	12257704
14"	300lbs	486	356	3	12257721
16"	600lbs	565	406	1.5	12257578
16"	300lbs	540	406	1.5	11934207
16"	150lbs	514	406	1.5	11934231
16"	150lbs	514	406	2	12257614
16"	300lbs	540	406	2	12257633
16"	600lbs	565	406	2	12257644
16"	600lbs	565	406	3	12257733
16"	300lbs	540	406	3	12257722
16"	150lbs	514	406	3	12134543
18"	600lbs	613	457	1.5	12257579
18"	150lbs	549	457	1.5	11934227
18"	300lbs	597	457	1.5	11934220
18"	300lbs	597	457	2	12257634
18"	600lbs	613	457	2	12257645
18"	150lbs	549	457	2	12257615
18"	300lbs	597	457	3	12257723
18"	150lbs	549	457	3	12257705
18"	600lbs	613	457	3	12257734
20"	600lbs	683	508	1.5	12257580
20"	150lbs	606	508	1.5	11934219
20"	300lbs	654	508	1.5	11934205
20"	300lbs	654	508	2	12257635
20"	600lbs	683	508	2	12257646
20"	150lbs	606	508	2	12257616
20"	300lbs	654	508	3	12257724
20"	600lbs	683	508	3	12257735
20"	150lbs	606	508	3	12134545
24"	600lbs	791	610	1.5	12257581
24"	150lbs	718	610	1.5	11934217
24"	300lbs	775	610	1.5	11934232
24"	150lbs	718	610	2	12257617
24"	300lbs	775	610	2	12257636
24"	600lbs	791	610	2	12257647

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal diameter	Flange pressure stage	Outer diameter	Inner diameter	Thickness	Article
		mm	mm	mm	
24"	600lbs	791	610	3	12257736
24"	150lbs	718	610	3	12257706
24"	300lbs	775	610	3	12257725

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.