



LEADER PTFE flange gasket CLIPPERLON 2120 ASME B16.21

Characteristics

Series: CLIPPERLON

Type: 2120

Norm: ASME B16.21

Material structure: PTFE, modified

Marking: Printed

Temperature range: -210 / 240 °C

Max. pressure: 85 bar

Suitable for medium: Chlorine Water < 5%

[7782-50-5], Air [compressed air], Food & Beverages, Refrigerants, Weak Alkalis, Strong Alkalis, Acids, Hydrocarbons, Chlorine, gaseous [7782-50-5], Low pressure steam, Solvents, Cryogenic, Alkalis, Weak Acids

Approval according to: Blow out VDI2200, Pamphlet 95 [CI], EC1935 [10/2011], TA-Luft

Application

- Recommended in: Chemical, Food & Beverages

Nominal diameter	Flange pressure stage	Outer diameter mm	Inner diameter mm	Thickness mm	Article
1/2"	150lbs	48	21	1.5	11934312
1/2"	300/600lbs	54	21	1.5	11934339
3/4"	150lbs	57	27	1.5	11934313
3/4"	300/600lbs	67	27	1.5	11934326
1"	150lbs	67	33	1.5	11934311
1"	300/600lbs	73	33	1.5	11934338
1.1/4"	150lbs	76	42	1.5	11934343
1.1/4"	300/600lbs	83	42	1.5	11934345
1.1/2"	300/600lbs	95	48	1.5	11934336
1.1/2"	150lbs	86	48	1.5	11934314
2"	300/600lbs	111	60	1.5	11934318
2"	150lbs	105	60	1.5	11934324
3"	300/600lbs	149	89	1.5	11934319
3"	150lbs	137	89	1.5	11934340
4"	300lbs	181	114	1.5	11934320
4"	150lbs	175	114	1.5	11934316
5"	300lbs	216	141	1.5	11934346
5"	150lbs	197	141	1.5	11934344
6"	300lbs	251	168	1.5	11934321
6"	150lbs	222	168	1.5	11934331
8"	150lbs	279	219	1.5	11934332
8"	300lbs	308	219	1.5	11934322
10"	300lbs	362	273	1.5	11934323
10"	150lbs	340	273	1.5	11934333
12"	150lbs	410	324	1.5	11934334
12"	300lbs	422	324	1.5	11934328
14"	150lbs	451	356	1.5	11934335
14"	300lbs	486	356	1.5	11934325
16"	300lbs	540	406	1.5	11934317
16"	150lbs	514	406	1.5	11934341
18"	150lbs	549	457	1.5	11934337
18"	300lbs	597	457	1.5	11934330
20"	300lbs	654	508	1.5	11934315
20"	150lbs	606	508	1.5	11934329
24"	150lbs	718	610	1.5	11934327
24"	300lbs	775	610	1.5	11934342

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.