


FRENZELIT Fibre flange gasket NOVAPRESS 815 ASME B16.21



Characteristics

Series: NOVAPRESS
Type: 815
Norm: ASME B16.21
With Inner eyelet: No
Fibre type: Aramid
Anti sticking layer: Yes
Temperature range: -50 / 150 °C
Max. pressure: 50 bar

Characteristics [2]

Suitable for medium: Grease, Weak Alkalis, Biodiesel, Natural gas, Oil, Refrigerants, Fuels, Lubricant, Solvents, Air (compressed air), Weak Acids
Approval according to: DVGW W270, DVGW, GL

Nominal diameter	Flange pressure stage	Outer diameter mm	Inner diameter mm	Thickness mm	Article
1/2"	300/600lbs	54	21	1.5	11043909
1/2"	150lbs	48	21	1.5	11043908
3/4"	150lbs	57	27	1.5	11043960
3/4"	300/600lbs	67	27	1.5	11043962
1"	300/600lbs	73	33	1.5	11043963
1"	150lbs	67	33	1.5	11043964
1.1/4"	150lbs	76	42	1.5	11043966
1.1/4"	300/600lbs	83	42	1.5	11043980
1.1/2"	300/600lbs	95	48	1.5	11043982
1.1/2"	150lbs	86	48	1.5	11043981
2"	150lbs	105	60	1.5	11084097
2"	300/600lbs	111	60	1.5	11043987
2.1/2"	150lbs	124	73	1.5	11043988
2.1/2"	300/600lbs	130	73	1.5	11043989
3"	300/600lbs	149	89	1.5	11044012
3"	150lbs	137	89	1.5	11044010
4"	600lbs	194	114	1.5	11914468
4"	150lbs	175	114	1.5	11044014
4"	300lbs	181	114	1.5	11044018
5"	600lbs	241	141	1.5	11914471
5"	150lbs	197	141	1.5	11044019
5"	300lbs	216	141	1.5	11044041
6"	600lbs	267	168	1.5	11914474
6"	300lbs	251	168	1.5	11044043
6"	150lbs	222	168	1.5	11044042
8"	300lbs	308	219	1.5	11044045
8"	600lbs	321	219	1.5	11914477
8"	150lbs	279	219	1.5	11044044
10"	150lbs	340	273	1.5	11044046
10"	600lbs	400	273	1.5	11914447
10"	300lbs	362	273	1.5	11044047
12"	300lbs	422	324	1.5	11044094
12"	150lbs	410	324	1.5	11044093
12"	600lbs	457	324	1.5	11914450
14"	150lbs	451	356	1.5	11044095
14"	300lbs	486	356	1.5	11044096
14"	600lbs	492	356	1.5	11914453
16"	600lbs	565	406	1.5	11914456
16"	150lbs	514	406	1.5	11044098

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal diameter	Flange pressure stage	Outer diameter	Inner diameter	Thickness	Article
		mm	mm	mm	
16"	300lbs	540	406	1.5	11044099
18"	150lbs	549	457	1.5	11127983
18"	300lbs	597	457	1.5	11127984
18"	600lbs	613	457	1.5	11914459
20"	150lbs	606	508	1.5	11044110
20"	600lbs	683	508	1.5	11914462
20"	300lbs	654	508	1.5	11044111
24"	300lbs	775	610	1.5	11044114
24"	600lbs	791	610	1.5	11914465
24"	150lbs	718	610	1.5	11044113

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.