



FRENZELIT Fibre flange gasket NOBAPRESS MULTI ASME B16.21

Characteristics

Series: NOBAPRESS

Type: MULTI

Norm: ASME B16.21

With Inner eyelet: No

Fibre type: Graphite, Aramid

Anti sticking layer: Yes

Temperature range: -100 / 250 °C

Max. pressure: 100 bar

Characteristics (2)

Suitable for medium: Refrigerants, Natural gas, Grease, Hydrocarbons, Oil, Weak Acids, Weak Alkalis, Lubricant, Low pressure steam, Fuels, Chlorine Water < 5% [7782-50-5], Solvents, Biodiesel, Air (compressed air), Chlorine, gaseous [7782-50-5]

Approval according to: BAM, BS7531 Grade X, DVGW, TA-Luft, GL

Nominal diameter	Flange pressure stage	Outer diameter	Inner diameter	Thickness	Article
		mm	mm	mm	
1/2"	150lbs	48	21	1.5	10002803
1/2"	300/600lbs	54	21	1.5	10002813
3/4"	300/600lbs	67	27	1.5	10002814
3/4"	150lbs	57	27	1.5	10002804
1"	300/600lbs	73	33	1.5	10002809
1"	150lbs	67	33	1.5	10002795
1.1/4"	150lbs	76	42	1.5	10002805
1.1/4"	300/600lbs	83	42	1.5	10002815
1.1/2"	300/600lbs	95	48	1.5	10002816
1.1/2"	150lbs	86	48	1.5	10002806
2"	300/600lbs	111	60	1.5	10002810
2"	150lbs	105	60	1.5	10002796
2.1/2"	150lbs	124	73	1.5	10002807
3"	150lbs	137	89	1.5	10002797
3"	300/600lbs	149	89	1.5	10002812
4"	300lbs	181	114	1.5	10002817
4"	150lbs	175	114	1.5	10002798
4"	600lbs	194	114	1.5	11914719
5"	600lbs	241	141	1.5	11914722
5"	150lbs	197	141	1.5	10002799
5"	300lbs	216	141	1.5	11914678
6"	600lbs	267	168	1.5	11914725
6"	300lbs	251	168	1.5	10002818
6"	150lbs	222	168	1.5	10002800
8"	150lbs	279	219	1.5	10002801
8"	300lbs	308	219	1.5	10002819
8"	600lbs	321	219	1.5	11914728
10"	600lbs	400	273	1.5	11914698
10"	300lbs	362	273	1.5	10002820
10"	150lbs	340	273	1.5	10002802
12"	300lbs	422	324	1.5	11272392
12"	150lbs	410	324	1.5	11117431
12"	600lbs	457	324	1.5	11914701
14"	300lbs	486	356	1.5	11272403
14"	150lbs	451	356	1.5	11117432
14"	600lbs	492	356	1.5	11914704
16"	300lbs	540	406	1.5	11272404
16"	150lbs	514	406	1.5	11272388

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal diameter	Flange pressure stage	Outer diameter	Inner diameter	Thickness	Article
		mm	mm	mm	
16"	600lbs	565	406	1.5	11914707
18"	300lbs	597	457	1.5	11272405
18"	150lbs	549	457	1.5	11272389
18"	600lbs	613	457	1.5	11914710
20"	300lbs	654	508	1.5	11272406
20"	150lbs	606	508	1.5	11272390
20"	600lbs	683	508	1.5	11914713
24"	300lbs	775	610	1.5	11272407
24"	150lbs	718	610	1.5	11272391
24"	600lbs	791	610	1.5	11914716

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.