



LEADER Fibre flange gasket FYBAR PT20 ASME B16.21

Characteristics

- Series:** FYBAR
- Type:** PT20
- Norm:** ASME B16.21
- With Inner eyelet:** No
- Fibre type:** Mineral fibre
- Anti sticking layer:** No
- Temperature range:** -30 / 130 °C
- Max. pressure:** 40 bar
- Suitable for medium:** Air (compressed air), Fuels, Grease, Oil

Nominal diameter	Flange pressure stage	Outer diameter mm	Inner diameter mm	Thickness mm	Article
1/2"	300/600lbs	54	21	1.5	11589710
1/2"	150lbs	48	21	1.5	11589671
3/4"	150lbs	57	27	1.5	11589672
3/4"	300/600lbs	67	27	1.5	11589711
1"	150lbs	67	33	1.5	11589693
1"	300/600lbs	73	33	1.5	11589712
1.1/4"	300/600lbs	83	42	1.5	11589713
1.1/4"	150lbs	76	42	1.5	11589694
1.1/2"	300/600lbs	95	48	1.5	11589714
1.1/2"	150lbs	86	48	1.5	11589695
2"	300/600lbs	111	60	1.5	11589715
2"	150lbs	105	60	1.5	11589696
2.1/2"	150lbs	124	73	1.5	11589697
2.1/2"	300/600lbs	130	73	1.5	11589716
3"	150lbs	137	89	1.5	11589698
3"	300/600lbs	149	89	1.5	11589717
4"	150lbs	175	114	1.5	11589699
4"	300lbs	181	114	1.5	11589718
4"	600lbs	194	114	1.5	12259527
5"	300lbs	216	141	1.5	11589719
5"	150lbs	197	141	1.5	11589700
5"	600lbs	241	141	1.5	12259528
6"	600lbs	267	168	1.5	12259529
6"	300lbs	251	168	1.5	11589720
6"	150lbs	222	168	1.5	11589701
8"	600lbs	321	219	1.5	12259530
8"	300lbs	308	219	1.5	11589721
8"	150lbs	279	219	1.5	11589702
10"	300lbs	362	273	1.5	11589722
10"	150lbs	340	273	1.5	11589703
10"	600lbs	400	273	1.5	12259531
12"	600lbs	457	324	1.5	12259532
12"	150lbs	410	324	1.5	11589704
12"	300lbs	422	324	1.5	11589723
14"	600lbs	492	356	1.5	12259533
14"	150lbs	451	356	1.5	11589705
14"	300lbs	486	356	1.5	11589724

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal diameter	Flange pressure stage	Outer diameter	Inner diameter	Thickness	Article
		mm	mm	mm	
16"	150lbs	514	406	1.5	11589706
16"	300lbs	540	406	1.5	11589725
16"	600lbs	565	406	1.5	12259534
18"	600lbs	613	457	1.5	12259535
18"	300lbs	597	457	1.5	11589726
18"	150lbs	549	457	1.5	11589707
20"	600lbs	683	508	1.5	12259536
20"	300lbs	654	508	1.5	11589727
20"	150lbs	606	508	1.5	11589708
24"	600lbs	791	610	1.5	12259537
24"	300lbs	775	610	1.5	11589728
24"	150lbs	718	610	1.5	11589709

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.