



ERIKS ELASTOMET OR NBR-ELL ASME B16.21

Characteristics

Series: ELASTOMET

Type: OR

Norm: ASME B16.21

Hardness (Sh A): 80 Sh A

Colour: Black

Temperature range: -25 / 70 °C

Max. pressure: 40 bar

Suitable for medium: Weak Alkalis, Water (process water), Water, Gases, Oil, Lubricant, Natural gas, Fuel oil, Weak Acids, Air (compressed air), Hydrocarbons, Fuels, Grease

Number of inserts	Nominal diameter	Flange pressure stage	Outer diameter	Inner diameter	Thickness	Flange standard	Article
			mm	mm	mm		
1	3/4"	150lbs	54	27	3/4	ASME B16.5 RF	10068451
1	1.1/2"	150lbs	83	48	3/4	ASME B16.5 RF	10068453
1	2"	150lbs	102	60	4/5	ASME B16.5 RF	10068458
1	3"	150lbs	133	89	4/5	ASME B16.5 RF	10068455
1	3.1/2"	150lbs	159	102	4/5	ASME B16.5 RF	14546794
1	4"	150lbs	171	115	5/6	ASME B16.5 RF	10068450
1	6"	150lbs	219	168	6/8	ASME B16.5 RF	10068457
1	8"	150lbs	276	219	6/8	ASME B16.5 RF	10068462
1	10"	150lbs	337	273	6/8	ASME B16.5 RF	10068459
1	12"	150lbs	406	325	6/8	ASME B16.5 RF	10068460
1	14"	150lbs	448	356	7/10	ASME B16.5 RF	10068464
1	16"	150lbs	512	406	7/10	ASME B16.5 RF	10068461

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.