



## ERIKS Rubber flange gasket NBR 70 SUPERBA ASME B16.21

### Characteristics

**Series:** NBR 70

**Type:** SUPERBA

**Norm:** ASME B16.21

**Hardness (Sh A):** 70 Sh A

**Colour:** Black

**Temperature range:** -20 / 80 °C

**Max. pressure:** 10 bar

**Suitable for medium:** Water, Alkalies, Air (compressed air), Lubricant, Fuels, Fuel oil, Grease, Hydrocarbons, Weak Alkalies, Natural gas, Weak Acids, Water (process water), Gases, Oil

| Number of inserts | Nominal diameter | Flange pressure stage | Outer diameter | Inner diameter | Thickness | Flange standard | Article  |
|-------------------|------------------|-----------------------|----------------|----------------|-----------|-----------------|----------|
|                   |                  |                       | mm             | mm             | mm        |                 |          |
| 0                 | 1/2"             | 150lbs                | 48             | 21             | 3         | ASME B16.5 RF   | 12252819 |
| 0                 | 3/4"             | 150lbs                | 57             | 27             | 3         | ASME B16.5 RF   | 12252820 |
| 0                 | 1"               | 150lbs                | 67             | 33             | 3         | ASME B16.5 RF   | 12252821 |
| 0                 | 1.1/4"           | 150lbs                | 76             | 42             | 3         | ASME B16.5 RF   | 12252822 |
| 0                 | 1.1/2"           | 150lbs                | 86             | 48             | 3         | ASME B16.5 RF   | 12252823 |
| 0                 | 2"               | 150lbs                | 105            | 60             | 3         | ASME B16.5 RF   | 12252824 |
| 0                 | 2.1/2"           | 150lbs                | 124            | 73             | 3         | ASME B16.5 RF   | 12252825 |
| 0                 | 3"               | 150lbs                | 137            | 89             | 3         | ASME B16.5 RF   | 12252826 |
| 0                 | 4"               | 150lbs                | 175            | 114            | 3         | ASME B16.5 RF   | 12252827 |
| 0                 | 5"               | 150lbs                | 197            | 141            | 3         | ASME B16.5 RF   | 12252828 |
| 0                 | 6"               | 150lbs                | 222            | 168            | 3         | ASME B16.5 RF   | 12252829 |
| 0                 | 8"               | 150lbs                | 279            | 219            | 3         | ASME B16.5 RF   | 12252830 |
| 0                 | 10"              | 150lbs                | 340            | 273            | 3         | ASME B16.5 RF   | 12252831 |
| 0                 | 12"              | 150lbs                | 410            | 324            | 3         | ASME B16.5 RF   | 12252832 |
| 0                 | 14"              | 150lbs                | 451            | 356            | 3         | ASME B16.5 RF   | 12252833 |
| 0                 | 16"              | 150lbs                | 514            | 406            | 3         | ASME B16.5 RF   | 12252834 |
| 0                 | 18"              | 150lbs                | 549            | 457            | 3         | ASME B16.5 RF   | 12252835 |
| 0                 | 20"              | 150lbs                | 606            | 508            | 3         | ASME B16.5 RF   | 12252836 |
| 0                 | 24"              | 150lbs                | 718            | 610            | 3         | ASME B16.5 RF   | 12252837 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.